

Code: DS-2CD1327G0-L(4MM)(C)

## IP CAMERA **DS-2CD1327G0-L(4MM)(C)** ColorVu - 1080p Hikvision

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Camera is according to IP67 Index of Protection norm.

**Attention!** The camera of the ColorVu series does not have a black and white mode. Thanks to fit the camera in a very sensitive sensor and the LED illuminator emitting visible light in white, the device allows to obtain a clear, colorful image in all lighting conditions.



|                                    |   |
|------------------------------------|---|
| Standard:                          | TCP/IP  |
| Sensor:                            | 1/2.8 " Progressive Scan CMOS   |
| Matrix size:                       | 2.1 Mpx   |
| Resolution:                        | 1920 x 1080 - 1080p ,<br>1280 x 720 - 720p  |
| Lens:                              | 4 mm  |
| View angle:                        | <ul style="list-style-type: none"> <li>• 84 ° (manufacturer data)</li> <li>• 80 ° (our tests result)</li> </ul>                               |
| White light LED illuminator range: | 30 m  |
| Memory card slot:                  | —   |
| Image compression method:          | H.265+ / H.265 / H.264+ / H.264 / MJPEG   |
| Alarm inputs / outputs:            | —   |
| Audio:                             | —   |
| Main stream frame rate:            | 25 fps @ 1080p  |
| Network interface:                 | 10/100 Base-T (RJ-45)   |
| Network protocols:                 | TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, IEEE 802.1x, QoS, IPv4/IPv6, Bonjour, UDP, SSL / TLS |



# DATA SHEET

|                                |   |
|--------------------------------|---|
| WEB Server:                    | Built-in  |
| Max. number of on-line users:  | 6   |
| ONVIF:                         | 18.12   |
| Main features:                 | <ul style="list-style-type: none"><li>• Possibility to turn off the LED illuminator</li><li>• D-WDR - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• Anti-Flicker - The technology eliminates the tiring eyes flickering image effect</li><li>• BLC - Back Light Compensation</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Mirror - Mirror image</li><li>• Motion Detection</li><li>• Configurable Privacy Zones</li><li>• Sharpness - sharper image outlines</li></ul> |
| Mobile phones support:         | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS: Free application <a href="#">Hik-Connect</a></li></ul>   |
| Default IP address:            | 192.168.1.64  |
| Default admin user / password: | admin / -<br>The administrator password should be set at the first start  |
| Web browser access ports:      | 80  |
| PC client access ports:        | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application   |
| Mobile client access ports:    | 8000  |
| Port ONVIF:                    | 80  |
| RTSP URL:                      | <ul style="list-style-type: none"><li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li><li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li></ul>  |
| Power supply:                  | <ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 400 mA</li></ul>   |
| Power consumption:             | $\leq 6.5 \text{ W @ PoE}$<br>$\leq 5 \text{ W @ 12 V DC}$  |
| Housing:                       | Dome, Aluminum + Plastic  |
| Color:                         | White   |
| "Index of Protection":         | IP67  |
| Vandal-proof:                  | —   |
| Operation temp:                | -30 °C ... 60 °C  |
| Weight:                        | 0.37 kg   |
| Dimensions:                    | Ø 110 x 104 mm  |
| Supported languages:           | English, Ukrainian  |
| Manufacturer / Brand:          | Hikvision   |
| SAP Code:                      | 311316793   |
| Guarantee:                     | <b>3 years</b>  |