

Code: HV/HDMI+HV-V2

CONVERTER **HV/HDMI+HV-V2**

The HV/HDMI+HV-V2 converter allows to connect the AHD/HD-CVI/HD-TVI/CVBS signals to the standard monitor or projector with a HDMI input. From the video signal the HV/HDMI+HV-V2 operates as a loop-through device, equipped with signal input and output.



Input:	1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8 Mpx (max)
Output:	<ul style="list-style-type: none"> • 1 x BNC - AHD / HD-CVI / HD-TVI / CVBS @ 8.3 Mpx (max), • 1 x HDMI @ 1080p 60 fps
Output signal possible standards:	PAL / NTSC
Supported resolutions:	<ul style="list-style-type: none"> • HDMI - 1080p • BNC - 8.3 Mpx (max)
OSD menu:	—
Main features:	<ul style="list-style-type: none"> • In the case of no input signal, the device displays a test chart (color bars) on the connected screen • Automatic recognition of the resolution - LED indication • USB cable 0.9 m (included) • BNC cable 0.9 m (included)
Power supply:	5 V DC / 2 A (power adapter included)
Weight:	0.18 kg
Dimensions:	108 x 95 x 25 mm
Guarantee:	2 years