

## DATA SHEET

## Code: WR5210-IDC ROUTER **WR5210-IDC** Wi-Fi 5 2.4 GHz, 5 GHz 300 Mbps + 867 Mbps DAHUA

With 867 Mbps wireless speeds over the crystal clear 5 GHz band and 300 Mbps over the 2.4 GHz band, WR5210-IDC offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Simple tasks such as sending e-mails or web browsing can be handled by the 2.4 GHz band while bandwidth intensive tasks like online gaming or HD video streaming can be processed by the 5 GHz band – all at the same time.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes. 6 external antennas provide stable omnidirectional signal and superior wireless coverage.

Supports 802.11ac standard - the next generation of Wi-Fi.



Frequency range:	2.4 GHz, 5 GHz
Antenna type:	6 x Omnidirectional antenna - Integrated
Standards:	IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz
Baud rates:	300 Mbps + 867 Mbps
LAN ports:	3 x 10/100/1000 Mbps LAN 1 x 10/100/1000 Mbps WAN
LED indicators:	Power, WLAN
DDNS:	-
DHCP server:	¥
Firmware update:	¥
Protections:	WPA-PSK/WPA2-PSK IP addresses filtering, MAC addresses filtering, SSID hiding
Management interface:	Web browser
Default IP address:	192.168.1.110



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60

WR5210-IDC



## DATA SHEET

Power supply:	12 V DC / 1 A (power adapter included)
Main features:	MU-MIMO - a multi-antenna transmission function that allows to increase the bandwidth and reliability of connection with the client of the network Beamforming (TxBF) - technology that allows to create a beam of radio waves in order to improve the quality of connection with client devices located further away from the signal source Firewall Internet access filtering Port Mapping SSID hiding Static routing Remote management Built-in 3-port switch WISP PPPoE parental control Guest Network - a separate and secure network for guests
Operation temp:	-10 °C 55 °C
Permissible relative humidity:	5 % 95 % (non-condensing)
Weight:	0.32 kg
Dimensions:	180 x 130 x 40 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years



WR5210-IDC