

Code: ITC415-PW6M-IZ-GN

IP CAMERA ANPR **ITC415-PW6M-IZ-GN** - 4 Mpx 2.7 ... 12 mm - MOTOZOOM DAHUA

The IP ANPR (Automatic Number Plate Recognition) Camera is designed for auto recognition of the vehicle number plates.

The used motozoom lens with 2.7 ... 12 mm focal length allows to remote view angle adjustment.

PoE powering possibility, compatible with the 802.3at standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/1.8 " CMOS
Matrix size:	4 Mpx
Resolution:	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p , 704 x 576 - D1
Lens:	2.7 ... 12 mm - Motozoom
View angle:	115 ° ... 48 °
Range of IR illumination:	12 m
Compression:	H.265 / H.264B / H.264M / H.264H / MJPEG
Main stream frame rate:	25 fps - 4 Mpx
Network interface:	100/1000 Base-T (RJ-45)
Network protocols:	IPv4/IPv6, HTTP, TCP/IP, UDP, NTP, DHCP, DNS



DATA SHEET

WEB Server:	Built-in
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Alarm inputs / outputs:	3 / 3
Audio:	<ul style="list-style-type: none">• External microphone input• Audio output• Bi-directional audio streaming support
RS-485 interface:	2 x
Mobile phones support:	—
Main features:	<ul style="list-style-type: none">• Motozoom lens• WDR - 96 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• WB - White Balance• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its• Built-in LPR Deep learning engine• Image analysis : License plate recognition, vehicle type recognition, vehicle logo, vehicle color, detection of vehicles without a license plate, recognition of the characteristics of the driver and front passenger, overlaying the image with time, address (channel position), lane (number/direction), plate (number and color), vehicle (speed, color, type)• Detection range : 3 ... 6 m - Width : 3 ... 4 m• Max. speed of a moving vehicle : 30 km/h• Protections : IP-MAC Binding, HTTPS, IEEE 802.1x, Access control• RS-232 interface• Video output (analog)
Power supply:	<ul style="list-style-type: none">• PoE (802.3at),• 12 V DC,• 24 V AC
Power consumption:	< 20 W
Housing:	Compact, Metal + Plastic
Color:	White + Black
"Index of Protection":	IP67
Vandal-proof:	—
Operation temp:	-30 °C ... 65 °C
Weight:	2.4 kg (with bracket)
Dimensions:	<ul style="list-style-type: none">• 297 x 108 x 124 mm (without bracket)• 487 x 186 x 124 mm (with bracket)
Supported languages:	English
Manufacturer / Brand:	DAHUA
Guarantee:	3 years