

Code: PFS3103-1GT1ET-60-V2

SWITCH POE **PFS3103-1GT1ET-60-V2** 2-PORT SFP DAHUA

The device is perfect to build a network of IP cameras with power supply in the PoE 802.3af / 802.3at standard.



LAN ports:	<ul style="list-style-type: none"> • 1 x RJ45 - 10/100 Base-T + Hi-PoE, • 1 x RJ45 - 10/100/1000 Base-T + Hi-PoE
Management via WWW / console:	—
Transmission speed:	<ul style="list-style-type: none"> • 10/100 Mbps - 1 x Port LAN • 10/100/1000 Mbps - 1 x Port LAN • 100/1000 Mbps - port SFP, Uplink
LED diodes:	Power, PoE, Link/Act
Maximal output power:	60 W / Channel
Maximal total power:	60 W
MAC addresses table:	8k
Main features:	<ul style="list-style-type: none"> • PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected • EXTEND mode - ports 2, 3 support transmission up to 250 m
Certificates:	CE
Operation temp:	-30 °C ... 65 °C
Power supply:	48 V ... 57 V DC / 1.13 A (power adapter included)



DATA SHEET

Weight:	0.28 kg
Dimensions:	115 x 85 x 30 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years