

Code: NVR4432-4KS2/I

IP DVR **NVR4432-4KS2/I** 32 CHANNELS DAHUA



Standard:	TCP/IP
Supported resolutions:	max. 16 Mpx - 4000 x 4000 px
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	32 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Supported hard drives:	4 x 10 TB SATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Center, IP Search, P2P, ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow
Bitrate:	max. 256 Mbps
Network functions:	Full support via network, Remote records copying, Web Server built-in
Mobile phones support:	Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"> • Android: Free application DMSS • iOS (iPhone): Free application DMSS <p>See how to configure the P2P function in Dahua recorders and how to enable the mobile application</p>
Default IP address:	192.168.1.108



DATA SHEET

Default admin user / password:	admin / -
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs:	16 / 4
PTZ control:	RS-485 - Pelco-P, Pelco-D and others IP Speed Dome Cameras
Motion Detection:	✓
RS-485 interface:	PTZ control function
RS-232 interface:	✓
USB:	1 pcs USB 2.0 1 pcs USB 3.0
Intelligent Image Analysis:	✓
Main features:	<ul style="list-style-type: none">• Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians,• Support for devices with the ANPR vehicle identification functions and face recognition,• Heat map - the selection in the image by corresponding colors the areas with different traffic• people counting• SMD PLUS - searching for an object classified as: human, motor vehicle,• face detection• Support for up to 10 face databases, including 20 000 face images• supports 6 types of facial attributes extraction• Face recognition and analysis in real time (up to 12 photos per second) :<ul style="list-style-type: none">- Comparison of faces with images from the database- Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask)• Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	100 ... 240 V AC, 50 / 60 Hz
Power consumption:	≤ 8 W (without HDD)
Operation temp:	-10 °C ... 55 °C
Weight:	4.32 kg
Dimensions:	440 x 411 x 76 mm
Supported languages:	Polish, English
Country of origin:	China
Manufacturer / Brand:	DAHUA



DATA SHEET

Guarantee:	3 years
------------	---------