

Code: APTI-H50C4-2812G

## AHD, HD-CVI, HD-TVI, PAL CAMERA **APTI-H50C4-2812G** 2Mpx / 5Mpx 2.8 ... 12 mm

Megapixel camera with 1/3" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. It enables the transmission of HD resolution images for even 500 m distance with keeping the low costs of the installation. During transmission there are no delays and is maintained the original, high quality image.

Setting the camera in PAL mode allows to obtain an image in 960H resolution. The appropriate signal format selection is done by tilting and holding the joystick for 5 s without entering to the OSD menu. Changing the signal to the NTSC in the camera causes loss of image in connected AHD/HD-CVI/HD-TVI recorder.

The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance). Camera is according to IP67 Index of Protection norm.

**Attention!** The camera is factory set to the resolution 2 Mpx (1080p).



Standard:	AHD, HD-CVI, HD-TVI, PAL
Sensor:	1/3 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	2592 x 1944 - 5 Mpx @ AHD / HD-TVI @ 20 fps, 12.5 fps , 2560 x 1440 - 4 Mpx @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps , 1920 x 1080 - 1080p @ AHD / HD-TVI / HD-CVI @ 25 fps, 30 fps , 960 x 576 - 960H @ PAL
Range of IR illumination:	40 m
IR illuminator power adjustment:	Automatic
Lens:	2.8 ... 12 mm
View angle:	<ul style="list-style-type: none"> <li>• 89 ° ... 27 ° (manufacturer data)</li> <li>• 80 ° ... 34 ° (our tests result)</li> </ul>
Video output:	1 Vpp 75 Ω, AHD / HD-CVI / HD-TVI / PAL - selectable by switch
Main features:	<ul style="list-style-type: none"> <li>• D-WDR - Wide Dynamic Range</li> <li>• 3D-DNR - Digital Noise Reduction</li> <li>• ICR - Movable InfraRed filter</li> <li>• AGC - Automatic Gain Control</li> <li>• Auto White Balance</li> <li>• Day/Night mode - configurable</li> <li>• Sharpness - sharper image outlines</li> </ul>
OSD menu:	✓



Power supply:	12 V DC / 410 mA
Power consumption:	≤ 4.9 W
Housing:	Compact - Metal
Color:	Graphite
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.67 kg
Dimensions:	210 x 88 x 84 mm
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years