

Code: TL-WR902AC

ROUTER **TL-WR902AC** 2.4 GHz, 5 GHz 300 Mbps + 433 Mbps TP-LINK

The TL-WR902AC mini-size router is ideal for home and travel use. Simple and easy installation and operation. The versatile USB port allows you to share files and connect a 3G/4G modem.

With 433 Mbps wireless speeds over the crystal clear 5 GHz band and 300 Mbps over the 2.4 GHz band, TL-WR902AC offers you the flexibility of 2 dedicated networks and ensures amazing wireless performance. Due to 5 operation modes, the TL-WR902AC is an extremely versatile device.

The TL-WR902AC ensures advanced access control and QoS, its DHCP server supports static assignment of IP addresses.



| | |
|-----------------------|--|
| Frequency range: | 2.4 GHz, 5 GHz |
| Antenna type: | 2 x Integrated, Internal antenna |
| Standards: | IEEE 802.11 b/g/n @ 2.4 GHz IEEE 802.11 a/n/ac @ 5 GHz |
| Baud rates: | 300 Mbps + 433 Mbps |
| LAN ports: | 1 x 10/100 Mbps (RJ-45) |
| LED indicators: | Power, INTERNET, WiFi, USB, WPS |
| Receiver sensitivity: | 2.4 GHz : <ul style="list-style-type: none"> • 11g 54M : -76 dBm • 11n HT20 MCS7 : -74 dBm • 11n HT40 MCS7 : -71 dBm 5 GHz : <ul style="list-style-type: none"> • 11a 54M : -76 dBm • 11ac VHT20 MCS8 : -70 dBm • 11ac VHT40 MCS9 : -65.5 dBm • 11ac VHT80 MCS9 : -61.5 dBm |
| Transmitter power: | < 20 dBm @ 2.4 GHz < 23 dBm @ 5 GHz |
| DDNS: | <ul style="list-style-type: none"> • No-IP • Comex • DynDNS |
| DHCP server: | ✓ |





DATA SHEET

| | |
|--------------------------------|---|
| Firmware update: | ✓ |
| Operation modes: | <ul style="list-style-type: none">• Router,• AP,• Range Extender,• Client,• WISP |
| Protections: | <ul style="list-style-type: none">• WEP, WPA/WPA2• SPI network firewall• Access control• IP-MAC Binding |
| Management interface: | Web browser, TP-LINK Tether |
| Main features: | <ul style="list-style-type: none">• IPv4/IPv6• parental control• Internet access filtering• WAN : Fixed, or dynamic IP address / PPPoE / PPTP / L2TP• QoS - mechanisms, which provide the high quality of transmission• Port forwarding : Virtual Server, Port Triggering, UPnP, DMZ• IPTV - IGMP• DHCP : DHCP server, DHCP client list• FTP server• RESET button• Mode button• Port USB 2.0• micro USB connector (power) |
| Power supply: | <ul style="list-style-type: none">• 5 V DC / 2 A (power adapter included)• from USB port |
| Operation temp: | 0 °C ... 40 °C |
| Permissible relative humidity: | 10 % ... 90 % (non-condensing) |
| Weight: | 0.068 kg |
| Dimensions: | 74 x 67 x 22 mm |
| Manufacturer / Brand: | TP-LINK |
| Guarantee: | 3 years |