

Code: ASC2204C-D

## ACCESS CONTROLLER **ASC2204C-D** DAHUA

The ASC2204C-D controller is intended to use in access control systems based on electrical control of door opening.



Number of served transitions:	4 (two-way)
Support:	DAHUA
Number of supported readers:	8 pcs
Battery backup support:	max. 7 Ah
Input lines:	20 pcs
Output lines:	8 pcs - Relay
Communication:	<ul style="list-style-type: none"><li>• 9x RS-485,</li><li>• Ethernet,</li><li>• 8x Wiegand 34/26</li></ul>
Power supply:	100 ... 240 V AC



# DATA SHEET

Main features:	<ul style="list-style-type: none"><li>• Support for 4 doors (20 inputs: 4x lock state, 4x door sensor, 4x exit button, 8x alarm line)</li><li>• 100000 indexed users</li><li>• History of 500000 events</li><li>• 128 General Purpose Schedules</li><li>• Function to prevent of multiple use of the same code/card to gain access (anti-passback)</li><li>• Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress</li><li>• Door Left Open and Door Forced Open alarms</li><li>• Tamper detection - opening the enclosure</li><li>• Watchdog built-in</li><li>• Remote programming from PC</li><li>• Real time clock with battery backup</li><li>• Metal housing - "Index of Protection" IP20, IK rating IK04</li></ul>
Operation temp:	-30 °C ... 60 °C
Permissible relative humidity:	max. 95 % (non-condensing)
Weight:	2.54 kg
Dimensions:	272 x 337 x 90 mm
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>