

Code: HC-RD2029WF

## HUNTING CAMERA **HC-RD2029WF**

Very good digital hunting camera, perfect to monitoring animals eg. in the forest, and also to surveillance houses, summer cottages, stores, etc. Built-in InfraRed illuminator enables recording video data also at night. Even with IR illuminator on, the device is completely invisible to the human eye, due to use the IR LEDs with 940 nm wavelength. Due to above the illuminator is completely invisible to the human eye. Camera is triggering by PIR detector and based on its settings can take one image or a few images or records a video sequence.

The hunting camera has been equipped with Bluetooth and Wi-Fi communication modules, thanks to which, using the mobile application, you can remotely configure the device and access the files on the memory card.

Minimal power consumption ensures very long and continuous operation time on batteries, even up to 6 months.

Hunting camera is full hermetic and resistant to very different environment conditions.

Warning! The hunting camera supports only SDHC cards and FAT32 file system. Remove the batteries before inserting/removing the SD card.



|                                  |   |
|----------------------------------|---|
| Sensor:                          | 5 Mpx CMOS  |
| View angle:                      | 80 °  |
| IR illuminator wavelength:       | 940 nm (invisible to the human eye)   |
| Range of IR illumination:        | 20 m  |
| Number of taking photos at once: | max. 10 still images  |
| Built-in monitor:                | 2.3 " Parameters and options display, still images playback   |
| Internal memory:                 | —   |
| External memory:                 | max. 128 GB SD memory card (not included)   |
| Still image resolution:          | 24 Mpx / 20 Mpx / 16 Mpx / 12 Mpx / 8 Mpx / 5 Mpx / 3 Mpx / 2 Mpx   |
| Video sequence resolution:       | 1728 x 1296 @ 30 fps<br>1920 x 1080 @ 30 fps<br>1280 x 720 @ 30 fps<br>848 x 480 @ 30 fps<br>640 x 360 @ 30 fps |
| Video sequence duration time:    | 5 ... 180 s   |



# DATA SHEET

|                                |  |
|--------------------------------|--|
| Day/night mode:                | ICR automatic filter   |
| PIR detection range:           | 20 m   |
| PIR detector:                  | with adjustable sensitivity (3 levels)   |
| Detection angle:               | 120 °  |
| Battery power supply:          | <ul style="list-style-type: none"><li>• 8 pcs LR6 (AA)</li><li>• DC 6V/12W power adapter (not included) - 1.3/3.5 mm plug</li></ul>  |
| Stand-by power consumption:    | < 0.25 mA - Battery supply is sufficient for approx. 6 months of operation in Standby mode   |
| Operation temp:                | -20 °C ... 60 °C   |
| Permissible relative humidity: | 5 ... 90 % (non-condensing)  |
| Main features:                 | <ul style="list-style-type: none"><li>• Time Lapse function - taking a photo at a specified time, regardless of whether there is movement (5s ... 24h),</li><li>• Built-in Bluetooth module that allows you to configure the device using the mobile application, without opening the housing,</li><li>• The ability to operate the device using a dedicated mobile application :<br/>Android: Free application <a href="#">Trail Camera Pro2</a><br/>iOS (iPhone): Free application <a href="#">Trail Camera Pro</a></li><li>• Built-in Wi-Fi module : IEEE 802.11 b/g/n, 2.4 GHz, Range : 10 m - AP mode,</li><li>• "Index of Protection" : IP66</li></ul> |
| Weight:                        | 0.31 kg  |
| Dimensions:                    | 136 x 101 x 77 mm  |
| Supported languages:           | Polish, English, French, Spanish   |
| Guarantee:                     | 2 years  |