

Code: APTI-XB0401H-S34

## AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **APTI-XB0401H-S34** 4 CHANNELS

The APTI-XB0401H-S34 digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and CVBS interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	AHD, HD-CVI, HD-TVI, PAL, TCP/IP
Video inputs:	4 pcs BNC - AHD / HD-CVI / HD-TVI / CVBS
Video outputs:	<ul style="list-style-type: none"> <li>• 1 pcs HDMI : 1920 x 1080 (max)</li> <li>• 1 pcs VGA</li> <li>• 1 pcs Composite Video (CVBS) - BNC socket</li> </ul>
Audio inputs:	<ul style="list-style-type: none"> <li>• 4 - Audio support via coaxial cable,</li> <li>• 2 pcs CINCH</li> </ul>
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Image records resolutions:	<ul style="list-style-type: none"> <li>• AHD / HD-TVI : 8M-N - 1920 x 2160 px, 5 Mpx - 2592 x 1944 px, 5M-N - 1296 x 1944 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 3 Mpx - 2048 x 1536 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px,</li> <li>• HD-CVI : 8M-N - 1920 x 2160 px, 4 Mpx - 2560 x 1440 px, 4M-N - 1280 x 1440 px, 1080p - 1920 x 1080 px, 720p - 1280 x 720 px,</li> <li>• CVBS : 960H - 960 x 576 px,</li> <li>• IP : max. 5 Mpx - 2592 x 1944 px</li> </ul>





# DATA SHEET

Recording speed adjustment:	5 Mpx IP @ 1 ... 25 fps 8M-N @ 1 ... 8 fps 5 Mpx @ 1 ... 6 fps 5M-N @ 1 ... 10 fps 4 Mpx @ 1 ... 8 fps 4M-N @ 1 ... 15 fps 3 Mpx @ 1 ... 9 fps 3M-N @ 1 ... 18 1080p @ 1 ... 15 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes:	<ul style="list-style-type: none"><li>• 4 x AHD / HD-CVI / HD-TVI / CVBS + 2 x IP max. 5 Mpx</li><li>• 2 x AHD / HD-CVI / HD-TVI / CVBS + 7 x IP max. 5 Mpx</li><li>• 16 x IP max. 5 Mpx</li></ul> All modes allow for any combination of the AHD, HD-CVI, HD-TVI, CVBS cameras
Recording modes:	Motion Detection, Schedule
Supported hard drives:	1 x 8 TB SATA
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, backward, fast, slow. Records playback from max. 4 channels in the same time
Network functions:	<ul style="list-style-type: none"><li>• Network Client Software (iVMS320): live view, playback and backup of the records</li><li>• IE browser: live view, playback and backup of the records and configuration of the recorder parameters</li></ul>
Mobile phones support:	Port no.: 6000 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">BitVision</a>, Android: Free application <a href="#">iVMS320</a></li><li>• iOS (iPhone): Free application <a href="#">BitVision</a>, iOS: Free application <a href="#">iVMS320</a></li></ul>
Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
Mobile client access ports:	80, 5000, 6000
Alarm inputs / outputs:	4 / 1
PTZ control:	Pelco-D, Pelco-P
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
USB:	2 pcs USB 2.0
Mouse support:	✓
IR remote controller in the set:	—
Power supply:	12 V DC / 2 A (power adapter included)
Color:	Black
Weight:	0.71 kg
Dimensions:	260 x 226 x 45 mm
Supported languages:	Polish, English, Bulgarian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Turkish, Hungarian, Italian



# DATA SHEET

---

Country of origin:	China
Manufacturer / Brand:	APTI
Guarantee:	2 years

