


Code: ASC2202B-D

## ACCESS CONTROLLER **ASC2202B-D** DAHUA

The ASC2202B-D controller is intended to use in access control systems based on electrical control of door opening.



Number of served transitions:	2 (two-way)
Support:	DAHUA
Number of supported readers:	4 pcs
Battery backup support:	—
Output lines:	4 pcs - Relay
Communication:	<ul style="list-style-type: none"> <li>• RS-485,</li> <li>• Ethernet,</li> <li>• Wiegand</li> </ul>
Power supply:	<ul style="list-style-type: none"> <li>• PoE (802.3af),</li> <li>• 12 V DC / 1.4 A</li> </ul>
Main features:	<ul style="list-style-type: none"> <li>• 100000 indexed users</li> <li>• History of 500000 events</li> <li>• Remote programming from PC</li> <li>• Function of protection against multiple use of the same card for access (anti-passback)</li> <li>• Counter of the door opening time with the possibility of sending an alarm signal after exceeding the set value</li> <li>• Automatic sending of alarm messages to the SmartPSS system or after entering a code, card or fingerprint defined as door opening under duress</li> <li>• Possibility to mount on a wall, or on the DIN TS-35 rail</li> </ul>
Default IP address:	192.168.0.2
Default admin user / password:	admin / - The administrator password should be set at the first start



# DATA SHEET

Operation temp:	-30 °C ... 60 °C
Permissible relative humidity:	max. 95 % (non-condensing)
Weight:	0.4 kg
Dimensions:	210 x 106 x 50 mm
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>