

DATA SHEET

Code: IPC-C27W-BAT IP CAMERA **IPC-C27W-BAT** Wi-Fi - 1080p 2.8 mm



The wireless IP camera allows you to record events on a micro SD card after motion is detected by the built-in PIR detector. The device allows you to save data to the cloud and remotely access them. Built-in lithium battery Li-Ion enables operation for a period of 6 months in places where there is no possibility of connecting cables.

Camera is according to IP66 Index of Protection norm.

Standard:	TCP/IP
Sensor:	1/2.9 " CMOS
Matrix size:	2.1 Mpx
Resolution:	1920 x 1080 - 1080p
Lens:	2.8 mm / F2.0
View angle:	 110 ° (manufacturer data) 102 ° (our tests result)
IR illuminator:	¥
Min. illumination:	0.01 Lux (color) 0.01 Lux (B/W)
RS-485 interface:	-
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Image compression method:	H.265 / H.264
ONVIF:	



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Alarm inputs / outputs:	_
Audio:	Microphone Speaker Bi-directional audio streaming support Noise reduction
Network interface:	2.4 GHz Wi-Fi - IEEE 802.11 b/g/n
Mobile phones support:	 Android: Free application <u>VicoHome</u> iOS (iPhone): Free application <u>VicoHome</u>
Default IP address:	-
Default user password:	-
Web browser access ports:	-
PC client access ports:	-
Main features:	 The device supports the cloud, which is also possible to access from the smartphone using the application Built-in PIR detector - Motion detection recording, Receive alarm notifications in the application when the camera detects motion, Alarm signaling via LED and/or siren (it is possible to manually start the alarm) Video recording to micro SD card with playback possibility IR illuminator ICR - Movable InfraRed filter Live image view Software update via network RESET button, Intelligent Image Analysis : Intelligent object recognition in the field of view (human / animal), area detection, package inspection
Power supply:	 Li-Ion battery - 4 V, 5200 mAh, Charging via micro USB port - 5 V / 1.5 A (power adapter not included)
Current consumption:	 0.42 mA Standby 220 / 550 mA Operation - Day/night mode
Backup time:	6 months
Charging time (recover to 100% capacity):	8 10 h
Housing:	Plastic
Color:	White + Black
"Index of Protection":	IP66
Vandal-proof:	-
Operation temp:	-10 °C 45 °C
Weight:	0.22 kg (without bracket)0.26 kg (with bracket)
Dimensions:	 89 x 59 x 58 mm (without bracket) 89 x 59 x 151 mm (with bracket)
Guarantee:	2 years



IPC-C27W-BAT