

Code: 24V/5A/GPV

## SWITCHING ADAPTER **24V/5A/GPV**

Hermetic power supply in a plastic housing.

Attention! If the power adaptor is using for continuous work (24H) the rated current of the adaptor should be less than 80% of the maximal current.

Please pay attention for proper cooling conditions of the power adaptor during work!



|                           |  |
|---------------------------|--|
| Adapter type:             | Switching  |
| Power voltage:            | 180 ... 277 V AC   |
| Frequency range:          | 47 ... 63 Hz   |
| Output voltage:           | 24 V DC  |
| Output voltage tolerance: | ± 5 %  |
| Maximal load:             | 5 A  |
| Output power:             | 120 W  |
| Efficiency:               | 89 %   |
| Number of outputs:        | 1 pcs  |
| Protections:              | <ul style="list-style-type: none"> <li>• Overload</li> <li>• Short-circuit</li> <li>• Overvoltage</li> <li>• Overheat</li> </ul> |
| Main features:            | <ul style="list-style-type: none"> <li>• Protection class : II</li> <li>• Box casing designed to wall mounting</li> </ul>        |
| Housing type:             | Plastic, Waterproof  |
| "Index of Protection":    | IP67   |
| Operation temp:           | -20 °C ... 70 °C   |



# DATA SHEET

---

|             |                  |
|-------------|------------------|
| Weight:     | 0.99 kg          |
| Dimensions: | 203 x 70 x 45 mm |
| Guarantee:  | <b>3 years</b>   |