

Code: NVR301-16X

NVR **NVR301-16X** 16 CHANNELS UNIVIEW

The NVR301-16X digital recorder is a professional device using in IP surveillance systems.



Standard:	TCP/IP
Supported resolutions:	max. 8.3 Mpx 4K UHD - 3840 x 2160 px
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	16 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	Ultra 265 / H.265 / H.264
Supported hard drives:	1 x 8 TB SATA
Recording modes:	Manual, Motion Detection, Schedule
Network protocols:	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, ONVIF
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Records playback from max. 16 channels in the same time 1/4/6/8/9/16 channel synchronous playback
Bitrate:	max. 64 Mbps
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on-line users Cloud update
ONVIF:	✓
Default admin user / password:	admin / 123456



DATA SHEET

Default IP address:	DHCP or 192.168.1.30
RTSP URL:	rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream
Web browser access ports:	80, 554
PC client access ports:	Port no.: 80 or access by a cloud (P2P) - PC: Free application EZStation
Mobile client access ports:	80
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) • Android: Free application EZView • iOS (iPhone): Free application EZView
Alarm inputs / outputs:	—
PTZ control:	PTZ Uniview cameras
Motion Detection:	✓
Intelligent Image Analysis:	✓
USB:	• 1 x USB 2.0 • 1 x USB 3.0
Mouse support:	✓
IR remote controller in the set:	—
Main features:	Functions implemented in cooperation between the recorder and cameras that support these functions • Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms • Motion Detection • Audio detection • IVS analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area, scene changing, abandoned/missing object, face detection, counting people in a given area
Power supply:	12 V DC / 2 A (power adapter included)
Weight:	0.91 kg
Dimensions:	260 x 247 x 47 mm
Supported languages:	Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian
Country of origin:	China
Manufacturer / Brand:	UNIVIEW
Guarantee:	3 years