

Code: BCS-B-DT43312(II)

AHD, HD-CVI, HD-TVI, PAL CAMERA **BCS-B-DT43312(II)** - 5 Mpx 3.3 ... 12 mm BCS BASIC

Megapixel camera with 1/2.9" CMOS sensor and AHD / HD-CVI / HD-TVI / PAL.

The AHD / HD-CVI / HD-TVI interface allows to transmission of analog video signal via coaxial cable in max. 8 Mpx (4K UHD) resolution. During transmission there are no delays and is maintained the original, high quality image.

In the case of video transmission using a twisted pair cable and matching transformers (balun), be aware of the possibility of signal reflections and interfering signals.



Standard:	AHD / HD-CVI / HD-TVI / CVBS
Sensor:	1/2.9 " Progressive Scan CMOS
Matrix size:	5 Mpx
Resolution:	2560 x 1944 - 5 Mpx @ 20 fps, AHD, HD-TVI 2560 x 1440 - 3.7 Mpx @ 25 fps, HD-CVI 960 x 576 - 960H, PAL
Range of IR illumination:	40 m
IR illuminator power adjustment:	Automatic
Lens:	3.3 ... 12 mm, F1.2
View angle:	<ul style="list-style-type: none"> • 120 ° ... 38 ° (manufacturer data) • 86 ° ... 33 ° (our tests result)
Video output:	AHD / HD-CVI / HD-TVI / CVBS, 1 Vpp / 75 Ω
Audio:	—
OSD menu:	✓



Main features:	<ul style="list-style-type: none">• D-WDR - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• ICR - Movable InfraRed filter• Day/night mode• Auto White Balance• AGC - Automatic Gain Control• OSD menu available via BCS-XVR recorder
Housing:	Compact, Metal
Color:	Dark graphite
"Index of Protection":	IP66
Vandal-proof:	—
Power supply:	12 V DC / 420 mA
Power consumption:	< 5 W
Operation temp:	-20 °C ... 60 °C
Weight:	0.86 kg
Dimensions:	277 x 81 x 83 mm
Supported languages:	English
Manufacturer / Brand:	BCS BASIC
Guarantee:	3 years