

Code: APTI-AI507V3-2812WP

IP CAMERA **APTI-AI507V3-2812WP** - 5 Mpx 2.8 ... 12 mm

IP camera with efficient H.264 / H.265 image compression algorithm for clear and smooth video streaming at maximal resolution of 5 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	TCP/IP
Sensor:	1/2.8 " SONY Starvis™ Back-illuminated CMOS
Matrix size:	5 Mpx
Resolution:	2592 x 1944 - 5 Mpx , 2560 x 1440 - 3.7 Mpx , 1920 x 1080 - 1080p , 1280 x 720 - 720p
Lens:	2.8 ... 12 mm, 5 Mpx
View angle:	<ul style="list-style-type: none"> • 93 ° ... 29 ° (manufacturer data) • 84 ° ... 34 ° (our tests result)
S/N ratio:	≥ 52 dB
Range of IR illumination:	30 m
Memory card slot:	—
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Main stream frame rate:	25 fps @ 5 Mpx



DATA SHEET

Network interface:	10/100 Base-T (RJ-45)
Alarm inputs / outputs:	—
Network protocols:	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, SMTP, UDP, SNMP
Audio:	<ul style="list-style-type: none">• External microphone input - Jack 3.5 mm socket• Audio output - Jack 3.5 mm socket• Bi-directional audio streaming support
WEB Server:	Built-in
Max. number of on-line users:	10
ONVIF:	19.12
RS-485 interface:	—
Mobile phones support:	Port no.: 80 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application BitVision• iOS (iPhone): Free application BitVision
Default IP address:	192.168.1.168
Default admin user / password:	admin / admin
Web browser access ports:	80
PC client access ports:	80
Mobile client access ports:	80
Port ONVIF:	80
RTSP URL:	rtsp://user:password@ip_address:554/0 - Main stream rtsp://user:password@ip_address:554/1 - Sub stream
Main features:	<ul style="list-style-type: none">• WDR - 120 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• Flicker Control - The technology eliminates the tiring eyes flickering image effect• ICR - Movable InfraRed filter• Privacy zones• Mirror - Mirror image• Day/Night mode - configurable• Possibility to change the resolution, quality and bit rate• Sharpness - sharper image outlines• Intelligent Image Analysis : intrusion, crossing the line (tripwire), video sabotage, detection of people gathering, motion detection based on human detection
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 470 mA
Power consumption:	≤ 5.6 W
Housing:	Dome - Metal
Color:	White
Vandal-proof:	—
"Index of Protection":	IP67
Operation temp:	-20 °C ... 60 °C
Weight:	0.61 kg



DATA SHEET

Dimensions:	Ø 120 x 97 mm
Supported languages:	Polish, English, French, Russian
Manufacturer / Brand:	APTI
Guarantee:	2 years