

Code: DS-KIS602(B)(O-STD)

VIDEO DOORPHONE KIT **DS-KIS602(B)(O-STD)** Hikvision

HIKVISION video doorphone set with 7" touch monitor and with the possibility of integration with both the alarm system and video monitoring. Video Doorphone is mounted in a surface housing.

Attention! To ensure proper operation, the "Extend" switch of the switch included in the set should be in the "Off" position.



| | |
|---------------------------|---|
| Compatibility: | IP Hikvision video doorphones II generation |
| Doorbell button: | 1 pcs |
| Sensor: | 2.1 Mpx CMOS |
| Camera resolution: | 1920 x 1080 - 1080p |
| Camera view angle: | 146 ° |
| Image compression method: | H.264 |
| IR illuminator: | ✓ |
| Ethernet: | 10/100 Mb/s |
| Network protocols: | TCP/IP, RTSP |
| Alarm inputs: | 4 pcs |
| Relay outputs: | 2 x NO/NC |
| Main features: | <ul style="list-style-type: none"> • Bidirectional communication, • Microphone built-in, • Speakers built-in, • Noise suppression and echo cancellation, • Tamper detection - removing from mounting surface, • Installation of DS-KD-xx series modules takes place in dedicated DS-KD-ACF series housings (flush-mounted housings) and DS-KD-ACW series housings (surface-mounted housings) • Power output : 12 V DC / 500 mA (max) |
| Power supply: | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC |

| | |
|------------------------|------------------|
| Power consumption: | ≤ 5 W |
| Operation temp: | -40 °C ... 60 °C |
| Housing: | Metal |
| Color: | Black |
| "Index of Protection": | IP65 |
| Weight: | 0.38 kg |
| Dimensions: | 100 x 98 x 44 mm |

INDOOR PANEL:

| | |
|---|--|
| Compatibility: | IP Hikvision modular video doorphones |
| Shield: | 7 " - capacitive touch screen |
| Resolution: | 1024 x 600 |
| Internal memory: | 128 MB (built-in) |
| Main features: | <ul style="list-style-type: none"> • Wi-Fi module - IEEE 802.11 b/g/n, • Microphone built-in, • Speakers built-in, • Bidirectional communication, • Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, • Automatically capture and save photos if there is no response to the bell button, • IP Hikvision cameras support, • The ability of direct communication between two or more panels, • Register a short voice message if there is no response to the bell button • Support for capturing a photo during video calls • The microSD cards support max. 32 GB, 16 GB included • The device is fully configurable via the iVMS4200 software. • In addition, the device has the ability to work with the Hik-Connect application on mobile devices |
| Controlling: | capacitive touch screen |
| Default administrator password: | — The administrator password should be set at the first start |
| Default password for securing the zone: | — |
| Alarm inputs: | 8 |
| Alarm outputs: | 2 |
| Power supply: | <ul style="list-style-type: none"> • PoE (802.3af), • 12 V DC |
| Power consumption: | ≤ 6 W |
| Color: | Black + Silver |
| Operation temp: | -10 °C ... 55 °C |
| Weight: | 0.34 kg |
| Dimensions: | 200 x 140 x 25 mm |

ENCLOSURE:

| | |
|----------------------------|----------|
| Number of mounted modules: | 1 pcs |
| Material: | Aluminum |





DATA SHEET

| | |
|----------------------|-------------------|
| Color: | Graphite |
| Weight: | 0.32 kg |
| External dimensions: | 117 x 107 x 37 mm |

SWITCH :

| | |
|-----------------------|---|
| Standards: | IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af |
| LAN ports: | <ul style="list-style-type: none">• 1 x RJ45 100 Base-T - Uplink,• 4 x 10/100 Base-T (4 x PoE (802.3af)) |
| LED diodes: | Power, PoE, Link/Act |
| Transmission speed: | 10 / 100 Mbps : 1 Port LAN + 4 LAN & PoE ports |
| Management: | — |
| Maximal output power: | 15 W / port PoE |
| Maximal total power: | 38 W |
| MAC addresses table: | 1k - Auto update of MAC addresses table |
| Operation modes: | <ul style="list-style-type: none">• Extend On : 250 m, 10 Mbps @ UTP cat. 5e, 6 - 1 ... 4 ports• Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6 |
| Operation temp: | 0 °C ... 40 °C |
| Power supply: | 48 V DC / 800 mA (power adapter included) |
| Weight: | 0.2 kg |
| Dimensions: | 132 x 95 x 28 mm |

General information:

| | |
|-----------------------|---|
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 305303906 |
| Guarantee: | 3 years |

