

Code: CS-HB-30H

MULTI-FUNCTIONAL CCTV TESTER **CS-HB-30H**

Multi-functional tester of AHD, HD-CVI, HD-TVI, IP cameras, analog cameras, Speed Dome (PTZ) cameras has implemented many additional functions, necessary during initialization of the CCTV installation system.



Video standard:	<ul style="list-style-type: none"> • AHD - 8 Mpx, • HD-CVI - 8 Mpx, • HD-TVI - 8 Mpx, • TCP/IP - 4K, • CVBS - PAL / NTSC
Display:	4 " - capacitive touch screen - 800 x 480 px
Video input:	1 pcs AHD / HD-CVI / HD-TVI / CVBS - BNC socket
Video output:	—
Port LAN:	2 pcs - PoE cameras and switches support
Audio input:	1 pcs Mini Jack
Audio output:	—
Video signal level meter:	—
Video signal generator:	✓
Serial ports:	RS-485



DATA SHEET

Protocols:	Support for over 30 RS485 protocols Pelco-D, Pelco-P, YAAN, YAAN-O, YAAN-1, SAMSUNG, PANASONIC, Lilin-FAST, Lilin-MLP2, MOLYNX, MINKING A01, Fastrax, CBC, LC-NEW, WV-CS850, SONY-EVI, LG-MULTIX, DAT-SD, VICON, Vcltp, DH-YTC 06, Santachi, Bosch OSRD, TeleEye DM2, HD 600, Hikvision, KALATEL ASC, AD 168(M-B), SAMSUNG SPD, Siemens, Cohu
Baud rates:	150, 300, 600, 1200, 2400, 4800, 9600, 19200, 38400, 115200 b/s
LAN (twisted-pair) or telephone cables testing:	UTP cables or phone lines connecting test with RJ-45 connectors
RS-485, RS-232 lines test:	Data analysis from control device (the commands are displayed in hexadecimal)
Wi-Fi Module:	2.4 GHz
Identification the wire in the group of wires:	—
Audio test:	✓
Digital multimeter:	—
Optical power measurement:	—
VLS (VFL) - Visual Fault Locator of fiber cable:	—
TDR reflectometer:	Detecting and locating a cable break (UTP only)
Operation as power source:	<ul style="list-style-type: none">• 12 V DC / 3 A• 48 V (PoE, LAN), 25.5 W
Battery power supply:	<ul style="list-style-type: none">• Li-Poly battery 7.4 V / 4000 mAh• 12 V DC / 2 A (power adapter included)
Estimated battery operation time:	max. 6 hours
Operation:	Graphic menu - touch control

<p>Main features:</p>	<ul style="list-style-type: none"> • AHD cameras test • HD-CVI cameras test • HD-TVI cameras test • PAL/NTSC cameras test • IP cameras test - Supported image compression methods : H.265, H.264 • Format support : 5 Mpx, 16 : 9 HD-CVI, DAHUA • Searching and view of IP cameras compatible with Onvif • Virtual IPC • Bitrate Calculator • DH test tool • Hik test tool • UNV Test Tool • HuaWei Tool • Motor units and PTZ (Speed Dome) cameras control • IP cameras view from embedded applications - iVMS-4500 HD, EZView, DH test tool, Hik test tool, UNV Test Tool, HW tool, gDMSS HD Lite, XMEye, Safire EasyView, XM Test Tool, Tiandy tool • Embedded Internet browser - Google Chrome • LAN connections monitoring • IP addresses scanner • PING - test the link using ICMP packets • Detection of the connected port in switch • LAN (twisted-pair) cables testing • PoE cameras and switches support • PoE power meter • DC 12V / 48V power source • Data monitor - serial port data analysis RS-485 • Audio test • Hotspot - Wi-Fi • Video recording to micro SD card with playback possibility (not included) • Tester Play - screen projection: tester, mobile phone and computer at the same time • Playback the records • Calculator • Flashlight built-in
<p>Operation temp:</p>	<p>-10 °C ... 50 °C</p>
<p>Permissible relative humidity:</p>	<p>30 % ... 90 %</p>
<p>Weight:</p>	<p>0.6 kg</p>
<p>Dimensions:</p>	<p>208 x 125 x 47 mm</p>
<p>Supported languages:</p>	<p>Polish, English, Czech, French, Spanish, German, Portuguese, Russian, Turkish, Italian</p>
<p>Guarantee:</p>	<p>2 years</p>

