

Code: DS-KIS604-S(C)

VIDEO DOORPHONE KIT **DS-KIS604-S(C)** Hikvision

HIKVISION video doorphone set with 7" touch monitor and with the possibility of integration with both the alarm system and video monitoring. Video Doorphone is mounted in a surface housing.

Attention! To ensure proper operation, the "Extend" switch of the switch included in the set should be in the "Off" position.



Compatibility:	IP Hikvision video doorphones II generation
Doorbell button:	1 pcs
proximity reader built-in:	13.56 MHz S50
Sensor:	2 Mpx
Camera resolution:	1920 x 1080 - 1080p
Camera view angle:	124 °
Image compression method:	H.264
Supported audio formats:	G.711
IR illuminator:	✓
Network interface:	<ul style="list-style-type: none"> • 10 / 100 Mbps Ethernet • WiFi
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network protocols:	TCP/IP, RTSP
Alarm inputs:	4 pcs



DATA SHEET

Relay outputs:	2 x NO/NC
RS-485:	✓
Main features:	<ul style="list-style-type: none">• Bidirectional communication,• Microphone built-in,• Speakers built-in,• Noise suppression and echo cancellation,• Tamper detection - removing from mounting surface,• True WDR - Wide Dynamic Range• BLC - Back Light Compensation• DNR - Digital Noise Reduction• Full support via network : WiFi / LAN• Video Doorphone is mounted in a surface housing• The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 830 mA (max)
Power consumption:	≤ 10 W (operation)
Operation temp:	-40 °C ... 53 °C
Housing:	Aluminum + Plastic, Protects against weather conditions
Color:	Black + Gray
Vandal-proof:	IK08
"Index of Protection":	IP65
Weight:	0.34 kg
Dimensions:	174 x 91 x 30 mm

INDOOR PANEL:

Compatibility:	IP Hikvision modular video doorphones
Shield:	7 " - capacitive touch screen
Resolution:	1024 x 600
Internal memory:	128 MB (built-in)
Main features:	<ul style="list-style-type: none">• Wi-Fi Module - IEEE 802.11 b/g/n,• Microphone built-in,• Speakers built-in,• Bidirectional communication,• Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume,• Automatically capture and save photos if there is no response to the bell button,• IP Hikvision cameras support,• The ability of direct communication between two or more panels,• Register a short voice message if there is no response to the bell button• Support for capturing a photo during video calls• The microSD cards support max. 32 GB, 16 GB included• The device is fully configurable via the iVMS4200 software.• In addition, the device has the ability to work with the Hik-Connect application on mobile devices
Controlling:	capacitive touch screen
Default administrator password:	— The administrator password should be set at the first start
Default password for securing the zone:	—



DATA SHEET

Alarm inputs:	8
Alarm outputs:	2
Power supply:	<ul style="list-style-type: none">• PoE (802.3af),• 12 V DC
Power consumption:	≤ 6 W
Color:	Black + Silver
Operation temp:	-10 °C ... 55 °C
Weight:	0.33 kg
Dimensions:	200 x 140 x 25 mm

ENCLOSURE:

Number of mounted modules:	1 pcs
Material:	Plastic
Color:	Black
Weight:	0.03 kg
External dimensions:	174 x 91 x 19 mm

SWITCH :

Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at
LAN ports:	<ul style="list-style-type: none">• 1 x RJ45 100 Base-T - Uplink,• 4 x 10/100 Base-T (4 x PoE (802.3af/at))• 1, 2 - High priority ports
LED diodes:	Power, PoE Max, Link/Act, PoE
Transmission speed:	10 / 100 Mbps : 1 Port LAN + 4 LAN & PoE ports
Management:	—
Maximal output power:	30 W / port PoE
Maximal total power:	35 W
MAC addresses table:	1k
Operation modes:	<ul style="list-style-type: none">• Extend On : 300 m, 10 Mbps @ UTP cat. 5e, 6 - 1 ... 4 ports• Extend Off : 100 m, 100 Mbps @ UTP cat. 5e, 6
Operation temp:	-10 °C ... 55 °C
Power supply:	48 V DC / 800 mA (power adapter included)
Weight:	0.2 kg
Dimensions:	105 x 86 x 28 mm

General information:

Supported languages:	Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Romanian, Serbian, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305303810





DATA SHEET

Guarantee:	3 years
------------	---------