

DATA SHEET

Code: DS-KH6351-WTE1

INDOOR PANEL Wi-Fi / IP **DS-KH6351-WTE1** Hikvision

The DS-KH6351-WTE1 panel has been designed to create a simple and effective system of local communication.

The device is dedicated to work with Hikvision IP video doorphones. It can be also used as simple alarm control panel, or notification module by the support 8 alarm inputs.

The device is fully configurable via the **iVMS4200** software. In addition, the device has the ability to work with the **Hik-Connect** application on mobile devices.



| Compatibility: | Hikvision IP Video Doorphones |
|------------------|---|
| Shield: | 7 " - capacitive touch screen |
| Resolution: | 1024 x 600 |
| Internal memory: | 128 MB (built-in) |
| Main features: | Wi-Fi module - IEEE 802.11 b/g/n, Microphone built-in, Speakers built-in, Bidirectional communication, Noise and echo reduction Smooth adjustment of monitor parameters: image brightness, ring tone volume and conversation volume, Automatically capture and save photos if there is no response to the bell button, IP Hikvision cameras support - max. 16, The ability of direct communication between two or more panels Support up to 17 door stations Register a short voice message if there is no response to the bell button Support for capturing a photo during video calls The microSD cards support max. 128 GB (not included) The device is fully configurable via the iVMS4200 software. In addition, the device has the ability to work with the Hik-Connect application on mobile devices Remote unlocking using client software or a mobile client |



DATA SHEET

| Controlling: | capacitive touch screen |
|---|--|
| Default administrator password: | The administrator password should be set at the first start |
| Default password for securing the zone: | - |
| Alarm inputs: | 8 |
| Alarm outputs: | 2 |
| Material: | Plastic (ABS) + Aluminum |
| Color: | Black |
| Power supply: | • 12 V DC, • IEEE 802.3af |
| Power consumption: | ≤ 3 W |
| Operation temp: | -10 °C 50 °C |
| Weight: | 0.35 kg |
| Dimensions: | 180 x 123 x 21 mm |
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Serbian, Turkish, Hungarian, Ukrainian, Vietnamese, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 305303851 |
| Guarantee: | 3 years |