

Code: BCS-B-NVR0401-4P(2.0)

## NVR **BCS-B-NVR0401-4P(2.0)** 4 CHANNELS, 4 PoE BCS BASIC



|                                     |  |
|-------------------------------------|--|
| Standard:                           | TCP/IP   |
| Supported resolutions:              | max. 8 Mpx 4K UHD - 3840 x 2160 px   |
| Video outputs:                      | 1 pcs HDMI 4K<br>1 pcs VGA   |
| Audio support:                      | 4 Channels - Audio from cameras  |
| Audio inputs:                       | —  |
| Audio outputs:                      | 1 pcs CINCH  |
| Image compression method:           | H.265+ / H.265 / H.264+ / H.264  |
| Bitrate:                            | max. 40 Mbps   |
| Supported hard drives:              | 1 x 6 TB SATA  |
| Recording modes:                    | Manual, Motion Detection, Schedule   |
| External storage devices backup:    | Backup to USB drive (pendrive, external drive)   |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>1/4 channel synchronous playback |
| Network interface:                  | 1 x RJ-45 10/100/1000 Base-TX  |
| Network functions:                  | Full support via network, Remote records copying, Web-Server built-in<br>max. 128 on-line users  |
| Network protocols:                  | P2P, UPnP, DHCP  |
| ONVIF:                              | ✓  |
| Default admin user / password:      | admin / 123456   |
| Default IP address:                 | DHCP or 192.168.1.30   |



# DATA SHEET

|                                  |  |
|----------------------------------|--|
| Web browser access ports:        | 80, 554  |
| PC client access ports:          | Port no.: 80 or access by a cloud (P2P)  |
| Mobile client access ports:      | 80   |
| Mobile phones support:           | Port no.: 80 or access by a cloud (P2P)<br>• Android: Free application <a href="#">BCS Manager</a><br>• iOS (iPhone): Free application <a href="#">BCS Manager</a> |
| RTSP URL:                        | rtsp://192.168.1.30:554/unicast/c1/s0/live - Main stream<br>rtsp://192.168.1.30:554/unicast/c1/s1/live - Sub stream  |
| Alarm inputs / outputs:          | —  |
| PTZ control:                     | IP Speed Dome Cameras  |
| Motion Detection:                | ✓  |
| USB:                             | 2 x USB 2.0  |
| Mouse support:                   | ✓  |
| IR remote controller in the set: | —  |
| Switch PoE:                      | 4-port PoE Switch built-in, 30 W / Channel, PoE (802.3af/at)   |
| Maximum total switch load:       | 54 W   |
| Power supply:                    | 48 V DC / 1.35 A (power adapter included)  |
| Power consumption:               | max. 9 W (without HDD)   |
| Weight:                          | 0.93 kg  |
| Dimensions:                      | 260 x 243 x 46 mm  |
| Supported languages:             | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovak, Italian  |
| Manufacturer / Brand:            | BCS BASIC  |
| Guarantee:                       | <b>3 years</b>   |