

DATA SHEET

Code: NVR5232-EI NVR NVR5232-EI 32 CHANNELS WizSense DAHUA



 $\ensuremath{\operatorname{NVR}}$ equipped with advanced functions of intelligent image analysis.

Standard:	TCP/IP
Supported resolutions:	max. 32 Mpx
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	32 Channels - Audio from camerasBi-directional audio streaming support
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	Smart H.265+ / H.265 / Smart H.264+ / H.264 / MJPEG
Bitrate:	max. 384 Mbps
Supported hard drives:	2 x 16 TB SATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	 Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) Smart Playback function Records playback from max. 32 channels in the same time @ 1080p (without AI) Records playback from max. 24 channels in the same time @ 1080p (AI)
Network interface:	1 x RJ-45 10/100/1000 Base-TX
Network functions:	Full support via network, Remote records copying, Web Server built-in
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, SNMP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, PPPoE, FTP, DDNS, Alarm Server, IP Search, Multicast, P2P, Auto Register
ONVIF:	21.12
Default IP address:	192.168.1.108



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Default admin user / password:	admin / - The administrator password should be set at the first start
Mobile phones support:	 Port no.: 37777 or access by a cloud (P2P) Android: Free application <u>DMSS</u> iOS (iPhone): Free application <u>DMSS</u> See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	 rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
USB:	• 1 pcs USB 2.0 • 1 pcs USB 3.0
Serial ports:	RS-485, RS-232
Alarm inputs / outputs:	4/2
PTZ control:	 IP Speed Dome Cameras RS-485 - PELCO-D/P and others
Motion Detection:	×
Intelligent Image Analysis:	✓
Main features:	 Intelligent Image Analysis : crossing the line (tripwire), intrusion, face detection SMD PLUS - searching for an object classified as: human, motor vehicle Filtering of false alarms based on the recognition of persons and vehicles Face recognition Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask)
Main features:	 Support for up to 20 face databases, including 20 000 face images In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity Privacy zones Cooperation with POS (Point of Sale) terminals
Main features:	 Support for up to 20 face databases, including 20 000 face images In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity Privacy zones Cooperation with POS (Point of Sale) terminals Functions implemented in cooperation between the recorder and cameras that support these functions : ANPR Authorized and unauthorized license plate lists: up to 20 000 records counting people / vehicles crowd gathering estimation heat map metadata handling - automatic photo taking and collection of information enabling
Main features:	 Support for up to 20 face databases, including 20 000 face images In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity Privacy zones Cooperation with POS (Point of Sale) terminals Functions implemented in cooperation between the recorder and cameras that support these functions : ANPR Authorized and unauthorized license plate lists: up to 20 000 records counting people / vehicles crowd gathering estimation heat map
	 Support for up to 20 face databases, including 20 000 face images In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number Intelligent face search by metadata of different targets or uploading pictures of faces to the device and comparing them with recorded faces by similarity Privacy zones Cooperation with POS (Point of Sale) terminals Functions implemented in cooperation between the recorder and cameras that support these functions : ANPR Authorized and unauthorized license plate lists: up to 20 000 records counting people / vehicles crowd gathering estimation heat map metadata handling - automatic photo taking and collection of information enabling the subsequent identification of people and vehicles that triggered the alarm (clothing, silhouette, face, features of motor and non-mechanical vehicles)



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



DATA SHEET

Power consumption:	max. 10 W (without HDD)
Operation temp:	-10 °C 55 °C
Weight:	1.53 kg
Dimensions:	375 x 284 x 55 mm
Supported languages:	Polish, English, Bulgarian, Czech, Finnish, Greek, Romanian, Serbian, Slovenian, Hungarian
Manufacturer / Brand:	DAHUA
Guarantee:	3 years

