

Code: IDS-7332HQHI-M4/S

AHD, HD-CVI, HD-TVI, CVBS, TCP/IP DVR **IDS-7332HQHI-M4/S** 32 CHANNELS +eSATA Hikvision

The digital recorder with AHD (Analog High Definition), HD-CVI (High Definition Composite Video Interface), HD-TVI (High Definition Transport Video Interface), TCP/IP and PAL interface is a professional device applicable in surveillance systems.

The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



Standard:	AHD, HD-CVI, HD-TVI, CVBS, TCP/IP
Video inputs:	32 pcs BNC
Video outputs:	1 pcs HDMI 1 pcs HDMI 4K 1 pcs VGA 1 pcs CVBS - BNC socket
Audio inputs:	4 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265 Pro+ / H.265 Pro / H.265 / H.264+ / H.264
Image records resolutions:	• HD-TVI : 3K Lite - 1480 x 1944 , • AHD, HD-TVI : 4M-N - 1280 x 1440 , 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • HD-CVI : 1080p - 1920 x 1080 , 1080N - 960 x 1080 , 720p - 1280 x 720 , • CVBS : 960H - 960 x 576 , D1 - 704 x 576 , • IP : max. 6 Mpx - 3072 x 2048



DATA SHEET

Recording speed adjustment:	6 Mpx IP @ 1 ... 25 fps 3K Lite @ 1 ... 12 fps 4M-N @ 1 ... 15 fps 1080p @ 1 ... 15 fps 1080N @ 1 ... 25 fps 720p @ 1 ... 25 fps 960H @ 1 ... 25 fps for each channel
Operation modes:	32 x HD-TVI / AHD / HD-CVI / PAL / IP + 16 x IP
Recording modes:	Manual, Sensor, Motion detection, Schedule
Supported hard drives:	4 x 12 TB SATA + 1 x eSATA
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	- Records searching: timeline or file list. Playback: forward, fast, slow. - Smart Search function - Playback max. 16 cameras in the same time @ 1080p
Network interface:	2 x RJ-45 - 10/100/1000 Base-T
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, partial configuration of the recorder parameters Web Server built-in max. 128 on-line users
Network protocols:	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP, HTTPS, ONVIF, SNMP
Default IP address:	DHCP or 192.168.1.64
Default admin user / password:	admin / -
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) - Android: Free application Hik-Connect - Android: Free application Hik-Connect
Web browser access ports:	80
PC client access ports:	554 RTSP, 8000
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	- rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream - rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream
USB:	2 pcs USB 2.0 1 pcs USB 3.0
Serial ports:	RS-485, RS-232
Alarm inputs / outputs:	16 / 4
PTZ control:	RS-485 PELCO-D/P Control compatible with coax HD-TVI Hikvision
Motion Detection:	2.0

Main features:	• DVR from the AcuSense series • Intelligent Image Analysis : intrusion, crossing the line (tripwire), Deep Learning technology • Filtering of false alarms based on the recognition of persons and vehicles • Smart motion detection (with recognizing people and vehicles) • Cooperation with POS (Point of Sale) terminals
Mouse support:	✓
IR remote controller in the set:	✓
Color:	Black
Power supply:	100 V ... 240 V AC @ 50 / 60 Hz
Power consumption:	max. 40 W (without HDD)
Weight:	4.95 kg
Dimensions:	440 x 405 x 76 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Greek, Spanish, Dutch, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	300228295
Guarantee:	3 years