

Code: INLEWA-41628

EVACUATION AND EMERGENCY LUMINAIRE **INLEWA-41628** Intelight

The INLEWA-41628 luminaire is designed to illuminate exits and indicate escape routes within the facility. The built-in control system allows you to use the device both as only emergency lighting and main light with the function of maintaining after a power failure. The high IP65 degree of protection allows the luminaire to be used in spaces with increased humidity and dust and guarantees trouble-free operation of the lamp after flooding, e.g. as a result of the activation of the fire protection system.

The lamp is equipped with a battery that allows it to maintain its operation for 3 hours after a power failure.



Rated voltage:	220 ... 240 V, 50 Hz
Power connector:	Spring terminals
Power consumption:	max. 4 W
Energy class:	F
Luminous flux:	104 lm
Light color:	Cool, 6500 K
CRI:	≥ 70
Main features:	<ul style="list-style-type: none"> • Surface mount, • Built-in battery supporting the operation of the lamp for 3 hours after a power failure • Battery : NiCd 3.6 V / 1800 mAh
Housing:	Plastic
"Index of Protection":	IP65
Strength class:	—
Color:	White
Operation temp:	10 °C ... 55 °C
Weight:	0.75 kg
Dimensions:	352 x 118 x 77 mm
Manufacturer / Brand:	Intelight
Guarantee:	2 years