

Code: PFS3110-8ET1GT1GF-96

## SWITCH POE **PFS3110-8ET1GT1GF-96** 8-PORT SFP DAHUA

The device is perfect to build a network of IP cameras with power supply in the PoE 802.3af / 802.3at standard.



LAN ports:	<ul style="list-style-type: none"> <li>• 8 x RJ45 10/100 Base-T ( 1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at) ),</li> <li>• 1 x RJ45 10/100/1000 Base-T - Uplink,</li> <li>• 1 x Port SFP 1000 Base-X - Uplink</li> </ul>
Management:	—
LED diodes:	Power, PoE, Link/Act, Uplink 1, Uplink 2
Transmission speed:	10 / 100 Mbps : 8 LAN & PoE ports , 10 / 100 / 1000 Mbps : 1 Port RJ45 (Uplink) , 1000 Mbps : 1 Port SFP (Uplink)
Maximal output power:	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE / PoE 802.3bt - Port 1</li> <li>• 30 W / port PoE 802.3af/at - 2 ... 8 ports</li> </ul>
Maximal total power:	96 W
MAC addresses table:	8k
Operation modes:	<ul style="list-style-type: none"> <li>• Extend On : 250 m, 10 Mbps</li> <li>• Extend Off : 100 m, 100 Mbps</li> <li>• PD Alive</li> </ul>
Main features:	<ul style="list-style-type: none"> <li>• PoE power mode - The device supports 8-pin power supply</li> <li>• Ports marked in red support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards with a maximum output power of 90 W per port - designed to power high power devices</li> <li>• Intelligent PoE power management - the device controls power consumption on individual ports</li> <li>• PoE Watchdog / PD Alive mode - monitoring of the ports that power PoE devices and automatic restart by cutting off the power supply when an unresponsive device is detected</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Industrial wide temperature design.</li> </ul>
Certificates:	CE, FCC
Housing:	Desktop, Metal



# DATA SHEET

Power supply:	53 V DC / 1.81 A (power adapter included)
Operation temp:	-10 °C ... 55 °C
Weight:	0.58 kg
Dimensions:	240 x 105 x 28 mm
Manufacturer / Brand:	DAHUA
Guarantee:	<b>5 years</b>