

Code: IPC3632SB-ADZK-I0

IP VANDALPROOF CAMERA **IPC3632SB-ADZK-I0** - 1080p 2.7 ... 13.5 mm - MOTOZOOM UNIVIEW

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install. The range of IR illumination according to the manufacturer data, depends on outer conditions (visibility - air transparency, environment, wall colors ie. scene reflectance).

The Uniview series product has been designed to minimize costs while maintaining high quality and ease of use.



| | |
|---------------------------|---|
| Standard: | TCP/IP |
| Sensor: | 1/2.8 " Progressive Scan CMOS |
| Matrix size: | 2.1 Mpx |
| Resolution: | 1920 x 1080 - 1080p , 1280 x 720 - 720p |
| Lens: | 2.7 ... 13.5 mm - Motozoom, AutoFocus |
| View angle: | <ul style="list-style-type: none"> • 107 ° ... 29 ° (manufacturer data) • 100 ° ... 28 ° (our tests result) |
| Range of IR illumination: | 40 m |
| RS-485 interface: | — |
| Memory card slot: | Micro SD memory cards up to 256GB support (possible local recording) |
| Image compression method: | Ultra 265 / H.265 / H.264 / MJPEG |
| Alarm inputs / outputs: | — |



DATA SHEET

| | |
|--------------------------------|--|
| Audio: | <ul style="list-style-type: none">• Microphone built-in• Audio transmission via network• Audio detection |
| Main stream frame rate: | 25 fps @ 1080p |
| Network interface: | 10/100 Base-TX (RJ-45) |
| Network protocols: | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, RTMP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, IEEE 802.1x, SNMP, QoS, SSL / TLS, SSH |
| WEB Server: | Built-in |
| Max. number of on-line users: | 32 |
| ONVIF: | ✓ |
| Mobile phones support: | Access by a cloud (P2P) <ul style="list-style-type: none">• Android: UNV-Link free application• iOS (iPhone): UNV-Link free application |
| Default IP address: | DHCP or 192.168.1.13 |
| Default admin user / password: | admin / 123456 |
| Web browser access ports: | 80, 554 |
| PC client access ports: | Port no.: 80 or access by a cloud (P2P) - PC: EZStation free application |
| Mobile client access ports: | 80 |
| Port ONVIF: | 80 |
| RTSP URL: | rtsp://192.168.1.13:554/unicast/c1/s0/live - Main stream rtsp://192.168.1.13:554/unicast/c1/s1/live - Sub stream |
| Main features: | <ul style="list-style-type: none">• WDR - 120 dB - Wide Dynamic Range• 2D-DNR, 3D-DNR - Digital Noise Reduction• F-DNR (Defog) - Reduction of image noise caused by precipitation• ROI - improve the quality of selected parts of image• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its• NAS - Network Attached Storage support• Corridor mode - useful for monitoring corridors, entrance gates and narrow rooms• BLC/HLC - Back Light / High Light Compensation• ICR - Movable InfraRed filter• Day/night mode• Possibility to change the resolution, quality and bit rate• Motion detection with human/vehicle silhouette recognition• Privacy zones - max. 4• Intelligent Image Analysis : intrusion, crossing the line (tripwire), detection of entry into the area / exit from the area, people counting, crowd gathering estimation |
| Power supply: | <ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 580 mA |
| Power consumption: | ≤ 7 W |
| Housing: | Dome - Metal |
| Color: | White |
| "Index of Protection": | IP67 |
| Vandal-proof: | IK10 |



DATA SHEET

| | |
|-----------------------|---|
| Operation temp: | -30 °C ... 60 °C |
| Weight: | 0.69 kg |
| Dimensions: | Ø 129 x 110 mm |
| Supported languages: | Polish, English, Czech, French, Spanish, Dutch, German, Portuguese, Slovenian, Hungarian, Italian |
| Manufacturer / Brand: | UNIVIEW |
| Guarantee: | 3 years |