

DATA SHEET

Code: NVR5832-EI

NVR **NVR5832-EI** 32 CHANNELS +eSATA DAHUA



 $\ensuremath{\mathsf{NVR}}$ equipped with advanced functions of intelligent image analysis.

Standard:	TCP/IP
Supported resolutions:	max. 32 Mpx
Video outputs:	2 pcs HDMI 4K 2 pcs VGA
Audio support:	32 Channels - Audio from cameras
Audio inputs:	1 pcs CINCH
Audio outputs:	2 pcs CINCH
Network interface:	2 x RJ-45 10/100/1000 Base-TX
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
USB:	2 pcs USB 2.0 2 pcs USB 3.0
Supported hard drives:	8 x 16 TB SATA III + 1 x eSATA Possibility of operation the disks in RAID 0/1/5/6/10 array
Recording modes:	Manual, Sensor, Motion detection, Schedule
Network protocols:	HTTP, HTTPS, TCP/IP, IPv4/IPv6, RTSP, UDP, SNMP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, PPPoE, FTP, DDNS, Alarm Server, IP Search, Multicast, P2P, Auto Register, ONVIF 21.12
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) max. 32 channel synchronous playback
Bitrate:	max. 384 Mbps
Network functions:	Full support via network, Remote records copying, Web Server built-in max. 128 on-line users



DATA SHEET

	Port no.: 37777 or access by a cloud (P2P)
Mobile phones support:	 Android: Free application <u>DMSS</u> iOS (iPhone): Free application <u>DMSS</u>
	See how to configure the P2P function in Dahua recorders and how to enable the mobile application
Default IP address:	192.168.1.108
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80, 37777
PC client access ports:	37777
Mobile client access ports:	37777
RTSP URL:	rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream rtsp://admin:hasło@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream
Alarm inputs / outputs:	16 / 8
PTZ control:	RS-485, PELCO-D/P IP Speed Dome Cameras
RS-232 interface:	~
Motion Detection:	~
Intelligent Image Analysis:	✓
intenigent intage Analysis:	*
Mouse support:	✓ ✓
Mouse support:	
Mouse support: IR remote controller in the set:	 Advanced peripheral protection functions: intrusion, crossing line with separate rules for vehicles and pedestrians, Support for devices with the ANPR vehicle identification functions and face recognition, Identification of the type of the observed object (human, vehicle), Face recognition and analysis in real time (up to 12 photos per second): Comparison of faces with images from the database Face analysis: determination of sex, age and characteristic elements of appearance (glasses, facial hair, mask) Real-time search of people on the basis of given side information in the range corresponding to features recognized by artificial intelligence of the device Face bases can be used globally or locally for one video channel - depending on the need In the base other than face photography, can also be stored such information as: name, sex, date of birth, nationality, address, ID number Recognition of people based on the characteristic elements of the outfit (type of clothes, clothes color, accessories) Recognition of cars based on color, body type, license plate color and brand Recognition of other vehicles not being cars Intelligent object search based on a photo - the recorder allows to upload a picture of a person or vehicle to search for it on a camera recording POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window SMD PLUS - searching for an object classified as: human, motor vehicle, non-motor



DATA SHEET

Manufacturer / Brand:	Italian DAHUA
Supported languages:	Polish, English, Bulgarian, Czech, Danish, Finnish, French, Greek, Spanish, Dutch, German, Portuguese, Russian, Romanian, Slovenian, Serbian, Swedish, Hungarian,
Dimensions:	440 x 458 x 89 mm - RACK 19", 2U