

Code: APTI-N0911-4P-I3

## NVR **APTI-N0911-4P-I3** 9 CHANNELS, 4 PoE

The APTI-N0911-4P-I3 digital recorder is a professional device applicable in surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity. The menu options layout has been designed for all users, even beginners can easy navigate and change parameters in DVR settings without any problem.



**Attention!** The built-in PoE switch only supports APTI cameras.

Standard:	TCP/IP
Supported resolutions:	max. 8 Mpx - 3840 x 2160 px, 4K UHD
Video outputs:	1 pcs HDMI 4K 1 pcs VGA
Audio support:	<ul style="list-style-type: none"> <li>• 9 Channels - Audio from cameras</li> <li>• Bi-directional audio streaming support</li> </ul>
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Bitrate:	80 Mbps
Supported hard drives:	1 x 8 TB SATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
External storage devices backup:	Records backup at (.avi) format to USB (pendrive)
Searching and playback the records:	Records searching: timeline or file list. Playback: forward, fast Playback max. 4 cameras in the same time @ 1080p
Network interface:	1 x RJ-45 10/100 Base-TX
Network functions:	Network Client Software and IE browser: live view, playback and backup of the records, configuration of the recorder parameters
Network protocols:	IPv6, TCP/IP, HTTP, HTTPS, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, P2P, PPPoE
ONVIF:	✓
Default IP address:	192.168.1.88
Default admin user / password:	admin / 12345



# DATA SHEET

Mobile phones support:	Access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: Free application <a href="#">BitVision</a>, Android: Free application <a href="#">iVMS320</a></li><li>• Android: Free application <a href="#">BitVision</a>, iOS: Free application <a href="#">iVMS320</a></li></ul>
Web browser access ports:	80, 5000, 554
PC client access ports:	80, 5000, 554
USB:	2 pcs USB 2.0
Serial ports:	—
Alarm inputs / outputs:	4 / 1
PTZ control:	IP Speed Dome Cameras
Motion Detection:	Split the screen into zones : 22 x 18 motion zones
Intelligent image analysis:	✓
Main features:	<ul style="list-style-type: none"><li>• Support for intelligent image analysis, available in cameras from the APTI-AI series</li><li>• D-ZOOM - Digital Zoom</li></ul>
Mouse support:	✓
IR remote controller in the set:	—
Switch PoE:	4-port PoE Switch built-in : 15 W / Channel - PoE (802.3af)
Maximum total switch load:	50 W
Power supply:	48 V DC / 1.36 A (power adapter included)
Power consumption:	≤ 10 W (without HDD)
Operation temp:	-10 °C ... 50 °C
Weight:	0.96 kg
Dimensions:	260 x 237 x 45 mm
Supported languages:	Polish, English, French, Spanish, German, Portuguese, Russian, Ukrainian, Italian
Manufacturer / Brand:	APTI
Guarantee:	2 years