

Code: LR2110-8ET-120-V2

INDUSTRIAL POE/EPOE SWITCH **LR2110-8ET-120-V2** 8-PORT SFP DAHUA

The LR2110-8ET-120-V2 PoE Switch is an industrial type device enabling fluent network transmission at rates 10 / 100 Mb/s. Devices of this type can be used in installations realized in industrial facilities in harsh environmental conditions like high or low temperature.

Attention! The SFP port requires the SFP module, which is available in our offer.

The device is equipped with ePoE technology which enables transmission up to 800 m at a speed of 10 Mb/s or 300 m at a speed of 100 Mb/s via cat. 5e twisted-pair.



LAN ports:	<ul style="list-style-type: none"> • 1 x port SFP 1000 Base-X - Uplink, • 1 x RJ45 10/100/1000 Base-T - Uplink, • 6 x RJ45 10/100 Base-T + ePoE / PoE (802.3af/at) - Color green, • 2 x RJ45 10/100 Base-T + PoE (802.3bt) / ePoE / PoE (802.3af/at) - Color : Red
Management:	—
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 Mbps - 6 LAN & PoE ports, • 10 / 100 / 1000 Mbps - 1 Port LAN - Uplink, • 1000 Mbps - 1 SFP ports - Uplink
Maximal output power:	<ul style="list-style-type: none"> • 30 W / port PoE @ PoE (802.3af/at) or ePoE, • 90 W @ PoE (802.3bt)
Maximal total power:	120 W
MAC addresses table:	8k
Main features:	<ul style="list-style-type: none"> • Auto-learning and Auto-aging functions support for MAC addresses • Data Flow Control • protection against lightning discharges and voltage differences and strokes between devices • Industrial wide temperature design. • Possibility to mount on a wall, or on the DIN TS-35 rail
LED diodes:	Power, Link/Act



DATA SHEET

Power supply:	54 V DC / 2.22 A (power adapter included)
Housing type:	DIN
Operation temp:	-30 °C ... 65 °C
Weight:	0.63 kg
Dimensions:	150 x 100 x 42 mm
Manufacturer / Brand:	DAHUA
Guarantee:	5 years