

Code: VM-802M

MONITOR HDMI, VGA, 2xCVBS, AUDIO, USB **VM-802M** 8 " VILUX

CCTV monitor with solid metal housing. The monitor is compatible with a 4:3 aspect ratio. Control functions are made by control keys placed on the top of the housing.

Due to its dimensions can be used in vehicles and at small areas, where high resistance to environment conditions is required.

The monitor is equipped with 3 mounting systems: mounting in the VESA standard, adjustable bracket and a set of frames for aesthetic, internal flush screen mounting. The integrated bracket enables to mount this monitor to vertical, horizontal and sloping surfaces (the tilt range of the bracket is equal 90°).

This model is equipped with all kinds of inputs, what allows to display an image from any kind of signals using in CCTV systems.



Screen size:	8 "
Native resolution:	1024 x 768 px
Aspect ratios:	4 : 3
Matrix type:	TFT-LCD color matrix, LED backlight, Glossy matrix
Contrast:	800 : 1
Brightness:	350 cd/m ²
Response time:	8 ms
Speakers built-in:	—
Signal connectors:	1 x HDMI 1 x VGA 1 x Video composite (Cinch socket) 2 x Audio (2 x cinch - L/R) 1 x USB 1 x Video composite (BNC socket) 1 x 2.1/5.5 mm socket 12 V DC
Number of displayed colors:	16.7 M

Refresh frequency:	60 Hz ... 75 Hz
Housing type:	Metal
Monitor mounting standard:	VESA 75
Robbery protection:	—
Parameters adjustment:	OSD - by monitor control keys
Designed to continuous operation 24/7:	✓
Main features:	<ul style="list-style-type: none">• Bracket enables to mount to flat, sloping or horizontal surfaces• Height adjustment• The set includes a set of frames for aesthetic, internal flush mounting of the screen• HDMI cable included
Power supply:	12 V DC / 1 A (power adapter included)
Power consumption:	≤ 12 W (operation)
Operation temp:	-10 °C ... 55 °C
Weight:	0.65 kg
Dimensions:	<ul style="list-style-type: none">• 189 x 147 x 35 mm (without stand)• 189 x 165 ... 177 x 102 mm (with stand)
Manufacturer / Brand:	VILUX
Guarantee:	2 years