

Code: DS-2CD2347G2H-LIU(2.8MM)(EF)

## IP CAMERA **DS-2CD2347G2H-LIU(2.8MM)(EF)** ColorVu - 4 Mpx Hikvision

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Camera is according to IP67 Index of Protection norm.

**Attention!** The device is equipped with Smart Hybrid Light / ColorVu technology, thanks to which the user has a choice of white light mode and IR (infrared) mode. When Smart Hybrid Light / ColorVu is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality.



Standard:	TCP/IP
Sensor:	1/1.8 " Progressive Scan CMOS
Matrix size:	4 Mpx
Resolution:	2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p
Lens:	2.8 mm
View angle:	<ul style="list-style-type: none"> <li>• 111 ° (manufacturer data)</li> <li>• 107 ° (our tests result)</li> </ul>
White light LED illuminator range:	40 m
Range of IR illumination:	40 m
Memory card slot:	Micro SD memory cards up to 512GB support (possible local recording)
Image compression method:	H.265+ / H.265 / H.264+ / H.264 / MJPEG
Alarm inputs / outputs:	—



# DATA SHEET

Audio:	<ul style="list-style-type: none"><li>• Microphone built-in</li><li>• Audio transmission via network</li><li>• Compliance with the AAC standard</li><li>• Noise and echo reduction</li></ul>
Main stream frame rate:	25 fps @ 4 Mpx
Network interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in
Max. number of on-line users:	6
ONVIF:	✓
Main features:	<ul style="list-style-type: none"><li>• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality</li><li>• Possibility to turn off the LED illuminator</li><li>• WDR - 130 dB - Wide Dynamic Range</li><li>• 3D-DNR - Digital Noise Reduction</li><li>• ROI - improve the quality of selected parts of image</li><li>• BLC - Back Light Compensation</li><li>• HLC - High Light Compensation (spot)</li><li>• Possibility to change the resolution, quality and bit rate</li><li>• Mirror - Mirror image</li><li>• Smart motion detection (with recognizing people and vehicles)</li><li>• Configurable Privacy Zones</li><li>• Sharpness - sharper image outlines</li><li>• Filtering of false alarms based on the recognition of persons and vehicles</li><li>• video tampering</li><li>• Intelligent Image Analysis : crossing the line (tripwire), intrusion, scene changing, detection of entry into the area / exit from the area - classification of people and vehicles, face detection</li></ul>
Mobile phones support:	<p>Port no.: 8000 or access by a cloud (P2P)</p> <ul style="list-style-type: none"><li>• Android: Free application <a href="#">Hik-Connect</a></li><li>• iOS: Free application <a href="#">Hik-Connect</a></li></ul>
Default IP address:	192.168.1.64
Default admin user / password:	admin / - The administrator password should be set at the first start
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application
Mobile client access ports:	8000
Port ONVIF:	80
RTSP URL:	<ul style="list-style-type: none"><li>• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/</li><li>• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/</li></ul>
Power supply:	<ul style="list-style-type: none"><li>• PoE (802.3af),</li><li>• 12 V DC / 420 mA</li></ul>
Power consumption:	<ul style="list-style-type: none"><li>• ≤ 6 W @ PoE</li><li>• ≤ 5 W @ 12 V DC</li></ul>
Housing:	Dome, Metal
Color:	White
"Index of Protection":	IP67



## DATA SHEET

Vandal-proof:	—
Operation temp:	-30 °C ... 60 °C
Weight:	0.77 kg
Dimensions:	Ø 138 x 115 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	311323589
Guarantee:	<b>3 years</b>