

Code: DS-KV9503-WBE1

WIRELESS VIDEO DOORPHONE **DS-KV9503-WBE1** Wi-Fi / IP Hikvision

Wi-Fi / IP video doorphone is dedicated to work with II generation IP Hikvision internal panels.

Video Doorphone is mounted in a surface housing.



Sensor:	2 x 2 Mpx
Resolution:	1920 x 1080
Camera view angle:	88 °
IR illuminator:	✓
LED illuminator:	—
PIR detector:	—
Display:	4.3 " IPS, 800 x 480 px - capacitive touch screen
Doorbell button:	1 pcs
proximity reader built-in:	13.56 MHz S50
Wireless transmission range:	The range limited only by the availability of the Wi-Fi network
Wi-Fi standard:	IEEE 802.11b / IEEE 802.11g / IEEE 802.11n
Network interface:	• Ethernet • Wi-Fi
RS-485 interface:	✓

Video output:	—
Video format:	H.264, H.265
Supported audio formats:	G.711
Alarm inputs:	4 pcs
Alarm outputs:	2 pcs - Relay (30V DC / 2A)
Main features:	• Lock control, • Face recognition - Memory of 10000 face templates, • 20 000 indexed users, • WDR - 120 dB - Wide Dynamic Range • Bidirectional communication, • Full support via network : WiFi / LAN, • Tamper detection - removing from mounting surface • Video Doorphone is mounted in a surface housing • The device has the ability to work with the Hik-Connect application for mobile devices, without the use of an internal panel
Power supply:	• PoE (802.3af) • 12 V DC / 1.5 A (power adapter included)
Power consumption:	< 6 W (operation)
Housing:	Aluminum + Plastic, Protects against weather conditions
Mount:	Surface-mounted
Color:	Black + Gray
"Index of Protection":	IP65
IK rating:	IK08
Operation temp:	-40 °C ... 60 °C
Weight:	0.40 kg
Dimensions:	182 x 85 x 32 mm
Supported languages:	Polish, English, French, Spanish, Dutch, German, Portuguese, Russian, Turkish, Hungarian, Vietnamese, Italian
Manufacturer / Brand:	Hikvision
SAP Code:	305303711
Guarantee:	3 years