

Code: DS-2CD2747G2HT-LIZS(2.8-12MM)(EF)

IP VANDALPROOF CAMERA **DS-2CD2747G2HT-LIZS(2.8-12MM)(EF)** ColorVu - 4 Mpx MOTOZOOM Hikvision

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 4 MPx.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.

Camera is according to IP67 Index of Protection norm.

Attention! The device is equipped with Smart Hybrid Light / ColorVu technology, thanks to which the user has a choice of white light mode and IR (infrared) mode. When Smart Hybrid Light / ColorVu is active, the white light will turn on automatically only when an object is detected in the monitored area, which effectively improves the image quality.



| | |
|------------------------------------|---|
| Standard: | TCP/IP |
| Sensor: | 1/1.8 " Progressive Scan CMOS |
| Matrix size: | 4 Mpx |
| Resolution: | 2688 x 1520 - 4 Mpx , 1920 x 1080 - 1080p 1280 x 720 - 720p |
| Lens: | 2.8 ... 12 mm Motozoom |
| View angle: | • 115 ° ... 42 ° (manufacturer data) • 105 ° ... 40 ° (our tests result) |
| Range of IR illumination: | 40 m |
| White light LED illuminator range: | 40 m |
| Memory card slot: | Micro SD memory cards up to 512GB support (possible local recording) |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Alarm inputs / outputs: | 1 / 1 |



DATA SHEET

| | |
|--------------------------------|--|
| Audio: | <ul style="list-style-type: none">• External microphone input• Audio output• Bi-directional audio streaming support• Noise suppression and echo cancellation• Compliance with the AAC standard |
| Main stream frame rate: | 25 fps @ 4 Mpx |
| Network interface: | 10/100 Base-T (RJ-45) |
| WEB Server: | Built-in |
| Max. number of on-line users: | 6 |
| ONVIF: | ✓ |
| Main features: | <ul style="list-style-type: none">• Smart Hybrid Light / ColorVu technology - IR or LED illuminator works in night mode. White light will turn on automatically only when an object is detected in the monitored area, which effectively improves image quality• Motozoom lens• Possibility to turn off the LED illuminator• WDR - 130 dB - Wide Dynamic Range• 3D-DNR - Digital Noise Reduction• ROI - improve the quality of selected parts of image• BLC - Back Light Compensation• HLC - High Light Compensation (spot)• NAS - Network Attached Storage support - allows to connect memory resources directly to the computer network• ANR - Automatic Network Replenishment allows to save image to the card when the network connection with DVR is break (network failure) and next synchronize its• Possibility to change the resolution, quality and bit rate• Horizontal mirror image• Smart motion detection (with recognizing people and vehicles)• Configurable Privacy Zones• Sharpness - sharper image outlines• video tampering• Intelligent Image Analysis : crossing the line (tripwire), intrusion, detection of entry into the area / exit from the area - classification of people and vehicles, scene changing, face detection |
| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) <ul style="list-style-type: none">• Android: Free application Hik-Connect• iOS: Free application Hik-Connect |
| Default IP address: | 192.168.1.64 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80 |
| PC client access ports: | Port no.: 8000 or access by a cloud (P2P) - iVMS-4200 application |
| Mobile client access ports: | 8000 |
| Port ONVIF: | 80 |
| RTSP URL: | <ul style="list-style-type: none">• Main stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/101/• Sub stream : rtsp://user:password@192.168.1.64:554/Streaming/Channels/102/ |
| Power supply: | <ul style="list-style-type: none">• PoE (802.3af),• 12 V DC / 880 mA |
| Power consumption: | <ul style="list-style-type: none">• ≤ 12.5 W @ PoE• ≤ 10.5 W @ 12 V DC |
| Housing: | Dome, Metal |



DATA SHEET

| | |
|------------------------|--|
| Color: | White |
| "Index of Protection": | IP67 |
| Vandal-proof: | IK10 |
| Operation temp: | -30 °C ... 60 °C |
| Weight: | 0.85 kg |
| Dimensions: | Ø 141 x 112 mm |
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, Finnish, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 311324000 |
| Guarantee: | 3 years |