

DATA SHEET

Code: DS-7608NXI-K1/ALARM4+1

NVR DS-7608NXI-K1/ALARM4+1 8 CHANNELS ACUSENSE Hikvision



 $\ensuremath{\mathsf{NVR}}$ equipped with advanced functions of intelligent image analysis.

| Standard: | TCP/IP |
|-------------------------------------|---|
| Supported resolutions: | max. 12 Mpx - 4000 x 3000 px |
| Video outputs: | 1 pcs HDMI 4K 1 pcs VGA There is a possibility to configure a SPOT function on one of the output |
| Audio support: | 8 Channels - Audio from cameras Bi-directional audio streaming support |
| Audio inputs: | 1 pcs CINCH |
| Audio outputs: | 1 pcs CINCH |
| Image compression method: | H.265+ / H.265 / H.264+ / H.264 |
| Supported hard drives: | 1 x 10 TB SATA |
| Recording modes: | Manual, Motion Detection, Schedule |
| Network protocols: | TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS, ONVIF |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow Advanced searching (to the one second accuracy) All channels synchronous playback, Smart Search function Records playback from max. 8 channels in the same time |
| Bitrate: | max. 80 Mbps |
| Network functions: | Live image view, Playback the records, Backup the records max. 128 on-line users - iVMS-4200 application |
| ONVIF: | ✓ |



DATA SHEET

| Mobile phones support: | Port no.: 8000 or access by a cloud (P2P) • Android: Free application <u>Hik-Connect</u> • iOS: Free application <u>Hik-Connect</u> |
|----------------------------------|--|
| Default IP address: | 192.168.1.64 |
| Default admin user / password: | admin / - The administrator password should be set at the first start |
| Web browser access ports: | 80, 8000 |
| PC client access ports: | 8000 |
| Mobile client access ports: | 8000 |
| RTSP URL: | • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream • rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream |
| Alarm inputs / outputs: | 4/1 |
| PTZ control: | ✓ |
| Motion Detection: | ✓ |
| Intelligent Image Analysis: | ✓ |
| Main features: | Smart motion detection (with recognizing people and vehicles) Filtering of false alarms based on the recognition of persons and vehicles face detection Comparison of faces with images from the database Support for up to 16 face databases, including 20 000 face images Smart search for a person based on a face photo NVR from the AcuSense series |
| USB: | 2 pcs USB 2.0 |
| Mouse support: | ✓ |
| IR remote controller in the set: | _ |
| Power supply: | 12 V DC / 1.5 A (power adapter included) |
| Weight: | 1.15 kg |
| Dimensions: | 315 x 245 x 48 mm |
| Supported languages: | Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Ukrainian, Hungarian, Italian |
| Country of origin: | China |
| Manufacturer / Brand: | Hikvision |
| SAP Code: | 303616139 |
| Guarantee: | 3 years |