

Code: DS-3E1510P-SI

SWITCH POE **DS-3E1510P-SI** 8-PORT SFP Hikvision

The DS-3E1510P-SI switch is designed for large streams of video data in the CCTV IP surveillance networks.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	• 8 x RJ45 10/100/1000 Base-T (8 x PoE (802.3af/at)), • 2 x port SFP 1000 Base-X
Transmission speed:	• 10 / 100 / 1000 Mbps - 8 LAN & PoE ports, • 1000 Mbps - 2 SFP ports - Uplink
Maximal output power:	30 W / port PoE
Maximal total power:	110 W
MAC addresses table:	8k
Management:	✓
Default IP address:	192.168.1.64
Default admin user / password:	admin / -
Operation modes:	• Extend On : 300 m, 10 Mbps • Extend Off : 100 m, 1000 Mbps

Main features:	• Switch is web managed • Configuration and management from the iVMS-4200 application • MDI/MDI-X auto detection feature - auto detecting the data transmission mode • View topology and network status • Data Flow Control • Storm Control function • Port mirroring function • Static link aggregation • QoS : Queue scheduling: SP, WRR, SP+WRR • VLAN support : 4094 • Port Isolation • Spanning Tree STP/RSTP • SNMPv1/v2c • Compliance with the LLDP protocol • Watchdog PoE • The device supports 8-pin power supply - wires : 1-2(-), 3-6(+), 4-5(+), 7-8(-) • Endspan mode support - wires : 1-2(-), 3-6(+) • Midspan mode support - wires : 4-5(+), 7-8(-) • Remote configuration • Remote update of software • System logs • Possibility to mount to the wall
LED diodes:	Power, Link/Act, PoE, PoE Max, 9 SFP, 10 SFP
Certificates:	CE, FCC, RoHS
Housing:	Metal, Desktop
Protections:	Overvoltage 6 kV - PoE ports
Power supply:	48 V DC / 2.5 A (power adapter included)
Power consumption:	max. 120 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.57 kg
Dimensions:	218 x 109 x 28 mm
Manufacturer / Brand:	Hikvision
SAP Code:	301802029
Guarantee:	3 years