

Code: SG4028

## SWITCH **SG4028** 24-PORT SFP DAHUA

The SG4028 switch is designed for large streams of video data in the CCTV IP surveillance networks.

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> <li>• 24 x RJ45 10/100/1000 Base-T,</li> <li>• 2 x RJ45 10/100/1000 Base-T - Uplink,</li> <li>• 2 x SFP 1000 Base-X - Uplink,</li> <li>• 1 x RJ45 - Console</li> </ul>
Management:	✓
LED diodes:	Link, Power, System
Transmission speed:	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps : 24 LAN ports + 2 RJ45 (Uplink) ports,</li> <li>• 1000 Mbps : 2 SFP (Uplink) ports</li> </ul>
MAC addresses table:	8k
Main features:	<ul style="list-style-type: none"> <li>• Switch is web managed</li> <li>• Static link aggregation</li> <li>• LACP</li> <li>• QoS - mechanisms, which provide the high quality of transmission</li> <li>• Compliance with the LLDP protocol</li> <li>• Spanning Tree STP/RSTP</li> <li>• IGMP Snooping</li> <li>• Supports up to 10 VLANs at the same time (for 4K ID VLAN addresses)</li> <li>• Data Flow Control (802.3x) - Full Duplex</li> <li>• DHCP client/server support</li> <li>• DHCP snooping support</li> <li>• IEEE 802.1x port authentication</li> <li>• RESET button</li> <li>• Console : RJ-45 output</li> <li>• MTBF (Mean Time Between Faults) : 467125.73 h</li> <li>• Protection against lightning discharges (common/differential) : 2 / 1 kV</li> <li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li> </ul>
Certificates:	CE
Housing:	RACK 19", 1U
Power supply:	100 A ... 240 V AC / 2 A
Power consumption:	max. 24 W
Operation temp:	-10 °C ... 55 °C



# DATA SHEET

---

Weight:	1.77 kg
Dimensions:	440 x 164 x 44 mm
Manufacturer / Brand:	DAHUA
Guarantee:	<b>3 years</b>