

Code: CUDY-LT400-OUTDOOR

ACCESS POINT 4G LTE +ROUTER **CUDY-LT400-OUTDOOR** 2.4 GHz 300 Mbps



The CUDY-LT400-OUTDOOR Wireless Router, operating in accordance with the 802.11 b/g/n standard, allows to share a network connection between several users in areas that are covered by 3G/4G signal.

Main applications include Internet accesses in small and medium size businesses, SOHO, and homes.

Frequency range:	2.4 GHz
Antenna type:	<ul style="list-style-type: none"> • 2 x Omnidirectional antenna Wi-Fi, Integrated, • 2 x Omnidirectional antenna 4G LTE, Outdoor - SMA type connectors
Standards:	<ul style="list-style-type: none"> • IEEE 802.11 b/g/n • 4G LTE
Baud rates:	<ul style="list-style-type: none"> • Wi-Fi : 300 Mbps, • LTE : 150 Mbps / 50 Mbps
LAN ports:	1 x 10/100 Mbps - LAN / WAN / PoE IN
Network type:	<ul style="list-style-type: none"> • 4G : LTE-FDD: B1/3/5/7/8/20/28 - 2100 / 1800 / 850 / 2600 / 900 / 800 / 700 MHz • 4G : LTE-TDD: B38/40/41 - 2600 / 2300 / 2500 MHz • 3G : WCDMA: B1/5/8 - 2100 / 850 / 900 MHz
LTE:	✓
QSS:	—
WDS:	—
DDNS:	✓
DHCP server:	✓



DATA SHEET

LED indicators:	Power, INTERNET, Ethernet, 2.4 GHz, LTE
SIM socket:	1 x nano SIM
Protections:	WPA-PSK, WPA2-PSK, WPA-PSK/WPA2-PSK
Firmware update:	✓
Management interface:	Web browser
Transmitter power:	< 20 dBm
Main features:	<ul style="list-style-type: none">• Nano SIM socket• RESET button• VPN networks: OpenVPN, WireGuard, IPSec, PPTP, L2TP, Zerotier VPN• DNS• Dynamic DNS• SMS personal messaging• WMM (Wi-Fi Multimedia)• Static / dynamic routing• DHCP client/server support, address reservation• NAT network firewall, Port forwarding, UPnP, DMZ• Access control• Remote management• IPv6 compliance• 4G bands lock
Power supply:	Passive PoE : 24 V DC / 0.5 A (power adapter included)
Operation temp:	-20 °C ... 60 °C
"Index of Protection":	IP65
Weight:	0.37 kg
Dimensions:	240 x 100 x 54 mm
Manufacturer / Brand:	CUDY
Guarantee:	2 years