

Code: AT-UPS2000-LED

UPS **AT-UPS2000-LED** 2000 VA EAST

The AT-UPS2000-LED UPS has been equipped with a number of advanced technologies ensuring active monitoring of the power supply network.

The line-interactive power supplies analyse the voltage, frequency and phase shift angle on a current basis, and filter the voltage transmitted to the connected devices. When a mains failure is detected, the UPS immediately switches to autonomous operation mode and continues to power the equipment using the energy accumulated in internal batteries.



Power adapter type:	Line-interactive
Nominal power:	1200 W
Apparent Power:	2000 VA
Input voltage:	145 ... 295 V AC
Input frequency:	50 / 60 Hz (auto detection)
Output voltage:	220 / 230 / 240 V AC \pm 10 % (Approximated Sine Wave)
Output frequency:	50 / 60 Hz \pm 1 %
Voltage adjustment:	—
Frequency adjustment:	—
Transfer time:	8 ms (typical), max. 10 ms
Charging time (recover to 90% capacity):	6 ... 8 hours
Battery:	2 pcs - 12V/9Ah
Number of outputs:	2 pcs CEE 7/3 (Schuko)
Management software:	—



DATA SHEET

Protections:	<ul style="list-style-type: none">• Fuse• Overvoltage
Operation state indication:	<ul style="list-style-type: none">• LED diodes,• Sound signaling
Main features:	<ul style="list-style-type: none">• Auto restart while AC is recovering• Excellent microprocessor control guarantees high reliability• COLD START function for manual switch to the battery power supply• Automatic Voltage Regulator (AVR)• Automatic battery charging in OFF mode• self test feature
Application:	<ul style="list-style-type: none">• network, servers, workstations• Surveillance Systems• small servers, DVRs, telecommunication equipment, VoIP working hardware, desktop computers, etc.
Housing type:	Tower
Operation temp. / Relative humidity:	0 °C ... 40 °C / 5 ... 90 %
Weight:	12.2 kg
Dimensions:	380 x 125 x 225 mm
Manufacturer / Brand:	EAST
Guarantee:	2 years