

Code: RG-ES126S-P-V2

SWITCH POE **RG-ES126S-P-V2** 24-PORT REYEE

Due to the reliability and ensuring high quality of transmission, the RG-ES126S-P-V2 24-port PoE switch is an ideal solution for applications in CCTV IP installations. 24 ports support the Power over Ethernet (PoE) function.



LAN ports:	• 24 x RJ45 10/100 Base-T (24 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink • 1 x port SFP - Uplink
Management:	—
Number of fan coolers:	2 pcs
LED diodes:	Power, PoE, Link/Act
Transmission speed:	• 10 / 100 Mbps : 24 LAN & PoE ports • 10 / 100 / 1000 Mbps : 2 Uplink ports • 1000 Mbps : 1 x port SFP Uplink
Maximal output power:	30 W / port PoE
Maximal total power:	370 W
Switching performance:	8.8 Gb/s
Packet redirection speed:	6.55 Mpps
MAC addresses table:	16k
Mobile phones support:	Android: Free application Ruijie Reyee iOS (iPhone): Free application Ruijie Reyee
Operation modes:	• Flow Control ON - Data flow control is enabled and all ports can communicate with each other, • Flow Control OFF - Data flow control is disabled and all ports can communicate with each other, • Port Isolation - 1 ... 24 ports are isolated from each other and separately work with the 25, 26 ports
Main features:	• View device status • protection against lightning discharges and voltage differences and strokes between devices • Grounding • IEEE802.3x Flow Control • MTBF (Mean Time Between Faults) > 200 000 h
Certificates:	CE, RoHS
Protections:	Protection against lightning discharges : 6 kV



DATA SHEET

Housing:	Desktop, Metal
Power supply:	100 V ... 240 V AC
Power consumption:	≤ 220 W
Operation temp:	0 °C ... 45 °C
Weight:	2.88 kg
Dimensions:	440 x 214 x 44 mm / RACK 19", 1U
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	3 years