

Code: RG-NBS5200-24SFP/8GT4XS

## Switch SFP **RG-NBS5200-24SFP/8GT4XS** 24-PORT REYEE

The RG-NBS5200-24SFP/8GT4XS switch is designed for large streams of video data in the CCTV IP surveillance networks.



LAN ports:	<ul style="list-style-type: none"> <li>• 24 x SFP ports</li> <li>• 8 x (RJ45) 10/100/1000 Mbps</li> <li>• 4 x SFP+ ports</li> </ul>
Management:	✓
Transmission speed:	<ul style="list-style-type: none"> <li>• 1000 Mbps - 24 x SFP ports</li> <li>• 10/100/1000 Mbps - 8 x Gigabit Ethernet</li> <li>• 10 Gb/s - 4 x port SFP+</li> </ul>
Switching capacity:	128 Gb/s
Forwarding rate:	96 Mpps
MAC addresses table:	16k
Certificates:	CE, RoHS
Number of fan coolers:	1
Mobile phones support:	Android: <a href="#">Ruijie Reyee</a> free application iOS (iPhone): <a href="#">Ruijie Reyee</a> free application
Jumbo Frame:	9 kB
Default IP address:	10.44.77.200





# DATA SHEET

Main features:	<ul style="list-style-type: none"><li>• Can be mounted in a Rack cabinet</li><li>• Switch is managed through the web and the cloud (Ruijie Reeye application)</li><li>• Access Control List - ACL package filtering based on source and destination IP addresses</li><li>• IEEE 802.1Q standard support, up to 4096 VLAN groups and 4K VIDs</li><li>• DHCP client</li><li>• BPDU Filtering/Guard</li><li>• Spanning Tree STP/RSTP</li><li>• Errdisable Recovery</li><li>• Up to 16 aggregation groups and up to 8 ports per group</li><li>• IGMP Snooping V1/V2/V3</li><li>• DHCP snooping support</li><li>• Port mirroring function</li><li>• Loop Protection</li><li>• IEEE802.3x Flow Control</li><li>• MTBF (Mean Time Between Faults) &gt; 200.000 h</li></ul>
Operation temp:	0 °C ... 50 °C
Permissible relative humidity:	10 % ... 90 % (non-condensing)
Protections:	Protection against lightning discharges : 6 kV
Power supply:	100 V ... 240 AC
Power consumption:	≤ 42 W
Weight:	3.59 kg
Dimensions:	440 x 267 x 63 mm
Manufacturer / Brand:	RUIJIE / REYEE
Guarantee:	<b>5 years</b>