

## DATA SHEET

## Code: BCS-V-NVR1602-A-4K-AI(2) NVR BCS-V-NVR1602-A-4K-AI(2) 16 CHANNELS BCS View

The BCS-V-NVR1602-A-4K-AI(2) digital recorder is a professional device using in IP surveillance systems. The H.265 / H.264 video compression standard using to record video data, allows to get the best possible quality of recorded image at minimal network transfer and disk storage capacity.



Standard:	TCP/IP
Supported resolutions:	max. 32 Mpx
Video outputs:	<ul> <li>1 pcs HDMI 4K</li> <li>1 pcs VGA</li> <li>1 pcs CVBS - BNC socket</li> </ul>
Audio support:	<ul><li>16 Channels - Audio from cameras,</li><li>Bi-directional audio streaming support</li></ul>
Audio inputs:	1 pcs CINCH
Audio outputs:	1 pcs CINCH
Image compression method:	H.265+ / H.265 / H.264+ / H.264
Bitrate:	max. 160 Mbps
Supported hard drives:	2 x 14 TB SATA
Recording modes:	Manual, Sensor, Motion detection, Schedule
External storage devices backup:	Backup to USB drive (pendrive, external drive)
Searching and playback the records:	Records searching: by time and events type. Records playback: forward, backward, fast, slow 1/4/9/16 channel synchronous playback
Network interface:	2 x RJ-45 10 / 100 / 1000 Mbps
Network functions:	Live image view, Playback the records, Backup the records Web Server built-in, CMS application max. 128 on-line users
Network protocols:	TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS
ONVIF:	¥
Default admin user / password:	admin / - The administrator password should be set at the first start



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60



## DATA SHEET

Default IP address:	192.168.1.64
Web browser access ports:	80
PC client access ports:	Port no.: 8000 or access by a cloud (P2P)
Mobile client access ports:	8000
Mobile phones support:	Port no.: 8000 or access by a cloud (P2P) • Android: Free application <u>BCS Manager</u> • iOS (iPhone): Free application <u>BCS Manager</u>
RTSP URL:	<ul> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no01/ - Main stream</li> <li>rtsp://user:password@192.168.1.64:554/Streaming/Channels/channel_no02/ - Sub stream</li> </ul>
USB:	1 pcs USB 2.0 1 pcs USB 3.0
Serial ports:	-
Alarm inputs / outputs:	4 / 1
PTZ control:	IP Speed Dome Cameras
Motion Detection:	✓
Intelligent Image Analysis:	✓
Main features:	<ul> <li>Intelligent Image Analysis : crossing the line (tripwire), intrusion, object detection (people, vehicle), face detection</li> <li>Face recognition</li> <li>Support for up to 16 face databases, including 50 000 face images</li> <li>POS - support the machines installed in the points of sales and displaying the date from them as overlaid text on selected channel window</li> <li>Functions implemented in cooperation between the recorder and cameras that support these functions :         <ul> <li>people counting</li> <li>License plate recognition</li> </ul> </li> </ul>
Mouse support:	✓
IR remote controller in the set:	-
Switch PoE:	-
Power supply:	12 V DC / 3.33 A (power adapter included)
Power consumption:	$\leq$ 30 W (without HDD)
Operation temp:	-10 °C 55 °C
Weight:	1.79 kg
Dimensions:	380 x 325 x 52 mm
Supported languages:	Polish, English, Bulgarian, Croatian, Czech, Danish, Estonian, French, Greek, Spanish, Dutch, Lithuanian, Latvian, German, Norwegian, Portuguese, Russian, Romanian, Serbian, Slovak, Slovenian, Swedish, Turkish, Hungarian, Italian
Manufacturer / Brand:	BCS View
Guarantee:	3 years



DELTA-OPTI Monika Matysiak; https://www.delta.poznan.pl POL; 60-713 Poznań; Graniczna 10 e-mail: delta-opti@delta.poznan.pl; tel: +(48) 61 864 69 60