

Code: S4100-8ET2GT-96-C

SWITCH POE **S4100-8ET2GT-96-C** 8-PORT DAHUA

Due to reliability and ensuring high quality of transmission, the S4100-8ET2GT-96-C 10/100M 8-port PoE desktop type switch is perfect solution for expanding home or office network. 8 ports support Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (DoLynk Care application).



LAN ports:	<ul style="list-style-type: none"> • 8 x RJ45 10/100 Base-T (1 x Hi-PoE (802.3bt) + 7 x PoE (802.3af/at)), • 2 x RJ45 10/100/1000 Base-T - Uplink
Transmission speed:	<ul style="list-style-type: none"> • 10 / 100 Mbps : 8 LAN & PoE ports, • 10 / 100 / 1000 Mbps : 2 Uplink ports
Maximal output power:	<ul style="list-style-type: none"> • 90 W / port Hi-PoE / PoE 802.3bt - Port 1 • 30 W / port PoE 802.3af/at - 2 ... 8 ports
Maximal total power:	96 W
MAC addresses table:	16k
Management:	✓
Operation modes:	Long Distance PoE On : 250 m, 10 Mbps @ UTP cat. 5e, 6
LED diodes:	Power, System, Link/Act, PoE
Main features:	<ul style="list-style-type: none"> • Switch is managed through the web and the cloud (DoLynk Care application) • PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-) • Intelligent management of Power Supply Unit power's output stage • protection against lightning discharges and voltage differences and strokes between devices • Watchdog PoE • Compliance with the LLDP protocol • Data Flow Control (802.3x) • DHCP client • RESET button • Kensington Lock • Possibility to mount to the wall
Certificates:	CE
Protections:	<ul style="list-style-type: none"> • Protection against lightning discharges (common/differential) : 4 / 2 kV • Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV



DATA SHEET

Housing:	Desktop, Metal
Power supply:	53 V DC / 1.81 A (power adapter included)
Power consumption:	max. 96 W
Operation temp:	-10 °C ... 55 °C
Weight:	0.49 kg
Dimensions:	190 x 100 x 30 mm
Manufacturer / Brand:	DAHUA
Guarantee:	3 years