

Code: DS-3T1310P-SI/HS

## SWITCH POE **DS-3T1310P-SI/HS** 8-PORT SFP Hikvision

Due to reliability and ensuring high quality of transmission, the DS-3T1310P-SI/HS 10/100 Mb/s 8-port PoE desktop type switch is perfect solution for expanding home or office network. 8 ports support Power over Ethernet (PoE) function.

DS-3T1310P-SI/HS is designed to mount on the DIN 35 mm rail.



|                                |                                                                                                                                                                                                |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LAN ports:                     | <ul style="list-style-type: none"> <li>• 8 x RJ45 10/100 Base-T ( 8 x PoE (802.3af/at) ),</li> <li>• 1 x RJ45 10/100/1000 Base-T - Uplink,</li> <li>• 1 x SFP 1000 Base-X - Uplink</li> </ul>  |
| Transmission speed:            | <ul style="list-style-type: none"> <li>• 10 / 100 Mbps - 8 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 Mbps - RJ45 (Uplink),</li> <li>• 1000 Mbps - SFP (Uplink)</li> </ul>                |
| Maximal output power:          | 30 W / port PoE                                                                                                                                                                                |
| Maximal total power:           | 110 W                                                                                                                                                                                          |
| MAC addresses table:           | 16k                                                                                                                                                                                            |
| Management:                    | ✓                                                                                                                                                                                              |
| Default IP address:            | 192.168.1.64                                                                                                                                                                                   |
| Default admin user / password: | admin / -                                                                                                                                                                                      |
| Operation modes:               | <ul style="list-style-type: none"> <li>• Extend - 1 ... 8 ports : 300 m, 10 Mbps @ UTP cat. 5e, 6</li> <li>• Port Isolation - 1 ... 8 ports</li> <li>• Watchdog PoE - 1 ... 8 ports</li> </ul> |
| LED diodes:                    | Power, Link/Act, PoE, PoE Max, G1, G2                                                                                                                                                          |

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main features:        | <ul style="list-style-type: none"> <li>• MDI/MDI-X auto detection feature - auto detecting the data transmission mode</li> <li>• View topology and network status</li> <li>• The device supports 8-pin power supply - wires : 1-2(-), 3-6(+), 4-5(+), 7-8(-)</li> <li>• Endspan mode support - wires : 1-2(-), 3-6(+)</li> <li>• Midspan mode support - wires : 4-5(+), 7-8(-)</li> <li>• Remote update of software</li> <li>• System logs</li> <li>• Data Flow Control</li> <li>• Watchdog function</li> <li>• Port mirroring function</li> <li>• Port isolation</li> <li>• QoS : Queue scheduling: SP, WRR, SP+WRR</li> <li>• VLAN : 4094 groups</li> <li>• Spanning Tree STP/RSTP</li> <li>• Spanning Tree ERPS</li> <li>• SNMPv1/v2c</li> <li>• Compliance with the LLDP protocol</li> <li>• DHCP</li> <li>• Devices for mounting on a DIN, TS-35 rail</li> <li>• Industrial wide temperature design.</li> </ul> |
| Certificates:         | CE, RoHS, FCC, WEEE, REACH                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Protections:          | —                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Housing:              | Metal, Desktop, DIN rail (TS-35)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Power supply:         | <ul style="list-style-type: none"> <li>• 48 ... 57 V DC - 2 inputs</li> <li>• 48 V AC / 2.5 A (power adapter included)</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Power consumption:    | max. 120 W                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Operation temp:       | -30 °C ... 65 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Weight:               | 0.596 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Dimensions:           | 205 x 125 x 42 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Manufacturer / Brand: | Hikvision                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| SAP Code:             | 301802343                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Guarantee:            | <b>3 years</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |