

Code: CDNP7ACC-ST-V2

DIGITAL DOORPHONE **CDNP7ACC-ST-V2** ACO

The CDNP doorphone panels are modern devices with digital dialing of the premises and code-based door opening.

Housing made of aluminum alloy additionally powder coated, provides maximum protection against vandalism and weather conditions.



| | |
|-----------------------------------|--|
| Compatibility: | ACO CDN |
| Method of mounting: | Can be flush or surface mounted depending on the frame selected |
| Operation mode: | Master / Slave |
| proximity reader built-in: | Unique EM 125kHz |
| The number of subscribers served: | 255 premises |
| Display: | LCD (heated) |
| Backlight: | White backlight |
| Inputs: | <ul style="list-style-type: none"> • 4 x screw connectors - Power connector : AC or DC • 1 x screw connection "INPUT" - External open button NO • 1 x screw connection - connection of audio signal from preceding panel • 2 x „EXTMOD” socket |
| Outputs: | <ul style="list-style-type: none"> • 2 x screw connectors „ELOCK” - Connection of a traditional, reversible electric door strike or CDN-PK relay module • 2 x screw connectors - Audio • 2 x screw connectors - connection of a second relay output |
| Line length: | 1000 m (max) |

| | |
|------------------------|---|
| Installation type: | Digital 2-wire |
| Main features: | <ul style="list-style-type: none"> • Acoustic and visual signalling of panel functions • Opening the door without answering the call • The control panel can operate either as a Master or as a Slave • Support for 255 4-digit tenant codes • Support for up to 6144 keyfobs • Acoustic information in the premises about the opening of the door • Adding and deleting proximity keyfobs with the "master" keyfob (separately for each premise) and with the "super master" keyfob (in all premises) • Ability to connect multiple active receivers under the same number • Porter function • Control of external devices, e.g. entrance gate, barrier, lighting, roller shutters |
| Power supply: | • 15 V DC / 400 mA or 12 V AC \pm 0.5 V |
| Power consumption: | ~ 6 W |
| Housing: | Aluminum - powder painted |
| "Index of Protection": | IP42 |
| Mechanical strength: | IK07 |
| Operation temp: | -20 °C ... 50 °C |
| Weight: | 0.416 kg |
| Dimensions: | 205 x 90 x 30 mm |
| Manufacturer / Brand: | ACO |
| Guarantee: | 2 years |