

Code: CS4228-24GT-240

## SWITCH POE **CS4228-24GT-240** 24-PORT SFP DAHUA

Due to reliability and ensuring high quality of transmission, the CS4228-24GT-240 10/100/1000 Mb/s 24-port PoE desktop type switch is perfect solution for expanding home or office network. 24 ports support the Power over Ethernet (PoE) function.

Switch is managed through the web and the cloud (DoLynk Care application).

Attention! The SFP port requires the SFP module, which is available in our offer.



LAN ports:	<ul style="list-style-type: none"> <li>• 24 x RJ45 10/100/1000 Base-T ( 2 x Hi-PoE (802.3bt) + 22 x PoE (802.3af/at) ),</li> <li>• 2 x RJ45 10/100/1000 Base-T - Uplink,</li> <li>• 2 x SFP 1000 Base-X - Uplink</li> </ul>
Management:	✓
Default IP address:	192.168.1.110
Default admin user / password:	admin / - The administrator password should be set at the first start
LED diodes:	Link, PoE, Power, System, 50 % PoE, 80 % PoE, 100 % PoE
Transmission speed:	<ul style="list-style-type: none"> <li>• 10 / 100 / 1000 Mbps : 24 LAN &amp; PoE ports,</li> <li>• 10 / 100 / 1000 Mbps : 2 RJ45 (Uplink) ports,</li> <li>• 1000 Mbps : 2 SFP (Uplink) ports</li> </ul>
Maximal output power:	<ul style="list-style-type: none"> <li>• 90 W / port Hi-PoE / PoE 802.3bt - 1, 2 ports</li> <li>• 30 W / port PoE 802.3af/at - 3 ... 24 ports</li> </ul>
Maximal total power:	240 W
MAC addresses table:	8k
Operation modes:	<ul style="list-style-type: none"> <li>• Long Distance PoE On : 250 m, 10 Mbps @ UTP cat. 5e, 6</li> </ul>
Main features:	<ul style="list-style-type: none"> <li>• Switch is managed through the web and the cloud (DoLynk Care application)</li> <li>• PoE power mode : The device supports 8-pin power supply - wires : 1-2(+), 3-6(-), 4-5(+), 7-8(-)</li> <li>• Intelligent management of Power Supply Unit power's output stage</li> <li>• protection against lightning discharges and voltage differences and strokes between devices</li> <li>• Watchdog PoE</li> <li>• Loop Protection</li> <li>• Compliance with the LLDP protocol</li> <li>• Spanning Tree STP/RSTP</li> <li>• Port Based VLAN : 32</li> <li>• Data Flow Control (802.3x)</li> <li>• DHCP client</li> <li>• RESET button</li> <li>• Can be mounted in a Rack 19" cabinet</li> </ul>



# DATA SHEET

Certificates:	CE
Protections:	<ul style="list-style-type: none"><li>• Protection against lightning discharges (common/differential) : 4 / 2 kV</li><li>• Protection against electrostatic discharge - Contact/Air (ESD/EMP) : 6 / 8 kV</li></ul>
Housing:	Metal
Power supply:	100 ... 240 V AC @ 47 ... 63 Hz
Power consumption:	max. 265 W
Operation temp:	-10 °C ... 55 °C
Weight:	2.52 kg
Dimensions:	440 x 220 x 44 mm, RACK 19", 1U
Manufacturer / Brand:	DAHUA
Guarantee:	<b>5 years</b>