

Code: SOT-5

## MOTOR UNIT DRIVER **SOT-5**

The SOT-5 motor unit driver is designed to cooperation with pan/tilt motor units and motozoom lenses. The driver executes the commands from devices with RS-485 telemetry transmitter, eg control panels, DVRs, video capture cards, video servers. The device casing is designed to outdoor mounting to a wall or to a mast with a tie.

ATTENTION! Switch the power off during cables connecting.



Number of operating motor units:	1 pcs
Camera power output:	12 V DC / 0.4 A
Current consumption in waiting mode:	50 mA
Maximal current load of directions outputs:	0.5 A
Maximal current load of ZOOM, FOCUS outputs:	0.1 A
RS-485 transmission baud rates:	2400, 4800, 9600 bps
Available protocols:	Pelco-D, Pelco-P, Delta-M
Short-circuit outputs protection:	✓
Motor unit control:	<ul style="list-style-type: none"> <li>• right</li> <li>• left</li> <li>• down</li> <li>• up</li> <li>• right down</li> <li>• right up</li> <li>• left down</li> <li>• left up</li> <li>• autoscan</li> </ul>
Camera control:	<ul style="list-style-type: none"> <li>• Zoom - focal length adjustment</li> <li>• Focus - sharpness adjustment</li> </ul>
Control socket type:	terminals
Power socket type:	terminals
Power supply:	24 V AC
Weight:	0.11 kg
Dimensions:	112 x 37 x 91 mm
Guarantee:	2 years