

Code: TC-C32PS SPEC:I3/E/Y/M/H/2.8MM/V4.2

IP CAMERA **TC-C32PS SPEC:I3/E/Y/M/H/2.8MM/V4.2** - 1080p 2.8 mm TIANDY

IP camera with efficient H.265 / H.264 image compression algorithm for clear and smooth video streaming at maximal resolution of 1080p.

PoE powering possibility, compatible with the 802.3af standard makes the device more universal and easier to install.



Standard:	IP
Resolution:	1920 x 1080 - 1080p , 1280 x 720 - 720p
Sensor:	1/2.8 " Progressive Scan CMOS
Lens:	2.8 mm
View angle:	101 ° (manufacturer data)
Range of IR illumination:	30 m
Memory card slot:	Micro SD card support up to 512GB
Image compression method:	S+265 / H.265 / H.264
Alarm inputs / outputs:	1 / 1
Audio:	• Microphone built-in • External microphone input • Audio output • Bi-directional audio streaming support • Audio detection
Main stream frame rate:	25 fps @ 1080p
Interface:	10/100 Base-T (RJ-45)
WEB Server:	Built-in
Max. number of on-line users:	2

ONVIF:	✓
Intelligent image analysis:	- crossing the line (tripwire) - classification of people and vehicles - intrusion - classification of people and vehicles
Main features:	- WDR - 120 dB - Wide Dynamic Range 3D-DNR - Digital Noise Reduction - ROI - improve the quality of selected parts of image - F-DNR (Defog) - Reduction of image noise caused by precipitation - NAS - Network Attached Storage support - BLC/HLC - Back Light / High Light Compensation - Possibility to change the resolution, quality and bit rate - Motion Detection - Configurable Privacy Zones - ICR - Movable InfraRed filter - Mirror - Mirror image
Mobile phones support:	Port: 3000 lub Access by a cloud (P2P) - Android: Free application EasyLive Plus - iOS (iPhone): Free application EasyLive Plus
Access from PC:	Port: 3000 lub Access by a cloud (P2P) PC: Free application Easy7 Smart Client Express
Default admin user / password:	admin / - The administrator password should be set at the first start
Default IP address:	192.168.1.2
Web browser access ports:	80, 443, 3000, 3001, 3002, 23002
Mobile client access ports:	3000, 3001
PC client access ports:	3000, 3001
Port ONVIF:	80
Power supply:	- PoE (802.3af), 12 V DC / 541 mA
Power consumption:	≤ 6.5 W @ 12 V DC ≤ 8 W @ PoE
Housing:	Dome, Metal
Color:	White
"Index of Protection":	IP66
Operation temp:	-40 °C ... 65 °C
Weight:	0.39 kg
Dimensions:	Ø 110 x 60 mm
Supported languages:	Polish, English, Albanian, Arabic, Spanish, Korean, French, Dutch, Hebrew, German, Russian, Portuguese, Thai, Turkish, Ukrainian, Vietnamese, Italian
Manufacturer / Brand:	TIANDY
Guarantee:	3 years