

Code: NVR1104HS-W-S2

## NVR **NVR1104HS-W-S2** Wi-Fi, 4 CHANNELS IMOU

Network Video Recorder allowing to operate with Wi-Fi IMOU cameras supported 802.11 b/g/n standards.



|                                  |  |
|----------------------------------|--|
| Standard:                        | IP   |
| Supported resolutions:           | max. 1080p - 1920 x 1080 px                    |
| Video outputs:                   | 1 pcs HDMI<br>1 pcs VGA                        |
| Audio support:                   | 4 Channels - Audio from cameras                |
| Audio inputs:                    | 1 pcs CINCH                                    |
| Audio outputs:                   | 1 pcs CINCH                                    |
| Image compression method:        | Smart H.265+ / H.265 / Smart H.264+ / H.264    |
| Bitrate:                         | max. 40 Mbps<br>max. 16 Mbps Wi-Fi             |
| Supported hard drives:           | 1 x 8 TB SATA                                  |
| Recording modes:                 | Manual, Motion Detection, Schedule             |
| External storage devices backup: | Backup to USB drive (pendrive, external drive) |



# DATA SHEET

|                                     |  |
|-------------------------------------|--|
| Searching and playback the records: | Records searching: by time and events type. Records playback: forward, backward, fast, slow<br>Advanced searching (to the one second accuracy)<br>1/4 channel synchronous playback   |
| Network interface:                  | <ul style="list-style-type: none"><li>• 1 x RJ-45 10/100 Base-TX</li><li>• 2.4 GHz Wi-Fi - IEEE 802.11 b/g/n</li></ul>   |
| Network functions:                  | <ul style="list-style-type: none"><li>• Built-in Wi-Fi module - Imou cameras support : Smart, auto-paring, Remote configuration, Remote management</li><li>• Full support via network, Remote records copying, Web-Server built-in</li></ul>                                   |
| ONVIF:                              | ✓  |
| Default IP address:                 | 192.168.1.108  |
| Default admin user / password:      | admin / -<br>The administrator password should be set at the first start   |
| Web browser access ports:           | 80, 37777  |
| PC client access ports:             | 37777  |
| Mobile client access ports:         | 37777  |
| Mobile phones support:              | Port no.: 37777 or access by a cloud (P2P) <ul style="list-style-type: none"><li>• Android: <a href="#">IMOU</a> free application</li><li>• iOS (iPhone): <a href="#">IMOU</a> free application</li></ul>  |
| RTSP URL:                           | rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=0 - Main stream<br>rtsp://admin:haslo@192.168.1.108:554/cam/realmonitor?channel=1&subtype=1 - Sub stream  |
| USB:                                | 2 pcs USB 2.0  |
| Serial ports:                       | —  |
| Alarm inputs / outputs:             | —  |
| PTZ control:                        | —  |
| Motion Detection:                   | ✓  |
| Intelligent image analysis:         | —  |
| Main features:                      | <ul style="list-style-type: none"><li>• Smart, auto-paring &lt; 120 s</li><li>• Alarm notifications</li><li>• 2x2 MIMO - MIMO technology - increases the throughput of wireless link (multiple antennas transmission)</li><li>• Operating range in open area : 100 m</li></ul> |
| Mouse support:                      | ✓  |
| IR remote controller in the set:    | —  |
| Power supply:                       | 12 V DC / 1.5 A (power adapter included)   |
| Power consumption:                  | ≤ 10 W (without HDD)   |
| Operation temp:                     | -10 °C ... 45 °C   |
| Weight:                             | 0.868 kg   |
| Dimensions:                         | 260 x 248 x 48 mm  |
| Supported languages:                | Polish, English  |



# DATA SHEET

---

|                       |         |
|-----------------------|---------|
| Manufacturer / Brand: | IMOU    |
| Guarantee:            | 2 years |

