

Code: APTI-W31C2-TUYA-V2

IP CAMERA **APTI-W31C2-TUYA-V2** Wi-Fi - 3 Mpx 3.6 mm

The cameras cooperating with the user-friendly Tuya platform have been designed with special care to simplify the configuration process and enable the user to create a simple and effective monitoring system.

Very easy operation via mobile devices (Android / iOS), allows the users for comfortable and remote operation, and also management of the camera. The used Wi-Fi module allows to remote communication with camera for max. distance up to 30 m.

Attention! Devices cooperating with the Tuya platform do not have a WEB interface. The camera works only with the mobile application (the camera does not work with recorders). Controlling the device and schedule settings is possible if the device has access to the Internet.



Standard:	IP
Resolution:	2048 x 1536 - 3 Mpx
Lens:	3.6 mm
View angle:	95 °
Range of IR illumination:	30 m
Audio:	• Microphone built-in, • Speaker built-in, • Audio transmission via network, • Bi-directional audio streaming support
Image compression method:	Smart H.264
Network interface:	• Wi-Fi - IEEE 802.11 b/g/n • 100 Base-T
ONVIF:	—
WEB Server:	—



DATA SHEET

Mobile phones support:	Access by a cloud (P2P) • The Tuya Smart free application on Android • The Tuya Smart free application on iOS
Default IP address:	DHCP
Web browser access ports:	—
PC client access ports:	—
Mobile client access ports:	—
Port ONVIF:	—
RTSP URL:	—
Memory card slot:	Micro SD memory cards up to 128GB support (possible local recording)
Main features:	• Wi-Fi module - IEEE 802.11 b/g/n, Range : 30 m (open area) • Video PUSH personal messaging • Motion Detection • Sound signaling • ICR - Movable InfraRed filter • RESET button
Power supply:	12 V DC / 670 mA (power adapter included)
Power consumption:	≤ 8 W
Housing:	Metal
"Index of Protection":	IP66
Weight:	0.333 kg
Dimensions:	195 x 62 x 62 mm
Operation temp:	-20 °C ... 55 °C
Supported languages:	English
Manufacturer / Brand:	APTI
Guarantee:	2 years